Casingjacks

Casingjacks LLC | sales@casingjack.com

Max pull tables

Data version 1.326cfcf0 | Build date 2026-11-17

Max pull

OD in	Weight lb/ft	Grade	Connection	Body lb	Joint lb	Lesser lb	P_allow lb	Body kN	Joint kN	Lesser kN	P_allow kN
4.5	9.5	J-55	STC	152,000	101,000	101,000	80,800	676.1	449.3	449.3	359.4
4.5	9.5	K-55	STC	152,000	112,000	112,000	89,600	676.1	498.2	498.2	398.6
4.5	9.5	M-65	STC	180,000	135,000	135,000	108,000	800.7	600.5	600.5	480.4
4.5	10.5	J-55	STC	166,000	132,000	132,000	105,600	738.4	587.2	587.2	469.7
4.5	10.5	J-55	BTC	166,000	203,000	166,000	132,800	738.4	903	738.4	590.7
4.5	10.5	K-55	STC	166,000	146,000	146,000	116,800	738.4	649.4	649.4	519.6
4.5	10.5	K-55	BTC	166,000	249,000	166,000	132,800	738.4	1,107.6	738.4	590.7
4.5	10.5	M-65	STC	195,000	154,000	154,000	123,200	867.4	685	685	548
4.5	10.5	M-65	BTC	195,000	231,000	195,000	156,000	867.4	1,027.5	867.4	693.9
4.5	11.6	J-55	STC	184,000	154,000	154,000	123,200	818.5	685	685	548
4.5	11.6	J-55	LTC	184,000	162,000	162,000	129,600	818.5	720.6	720.6	576.5
4.5	11.6	J-55	BTC	184,000	225,000	184,000	147,200	818.5	1,000.8	818.5	654.8
4.5	11.6	K-55	STC	184,000	170,000	170,000	136,000	818.5	756.2	756.2	605
4.5	11.6	K-55	LTC	184,000	180,000	180,000	144,000	818.5	800.7	800.7	640.5
4.5	11.6	K-55	BTC	184,000	277,000	184,000	147,200	818.5	1,232.2	818.5	654.8
4.5	11.6	M-65	STC	217,000	179,000	179,000	143,200	965.3	796.2	796.2	637
4.5	11.6	M-65	LTC	217,000	188,000	188,000	150,400	965.3	836.3	836.3	669
4.5	11.6	M-65	BTC	217,000	256,000	217,000	173,600	965.3	1,138.7	965.3	772.2
4.5	11.6	L-80	LTC	267,000	212,000	212,000	169,600	1,187.7	943	943	754.4
4.5	11.6	L-80	BTC	267,000	291,000	267,000	213,600	1,187.7	1,294.4	1,187.7	950.1
4.5	11.6	N-80	LTC	267,000	223,000	223,000	178,400	1,187.7	992	992	793.6
4.5	11.6	N-80	BTC	267,000	304,000	267,000	213,600	1,187.7	1,352.3	1,187.7	950.1
4.5	11.6	C-90	LTC	300,000	223,000	223,000	178,400	1,334.5	992	992	793.6
4.5	11.6	C-90	BTC	300,000	309,000	300,000	240,000	1,334.5	1,374.5	1,334.5	1,067.6
4.5	11.6	C-95	LTC	317,000	234,000	234,000	187,200	1,410.1	1,040.9	1,040.9	832.7

Check every figure against your own pipe records before you pull.

Casingjacks

Casingjacks LLC | sales@casingjack.com

Max pull tables

Data version 1.326cfcf0 | Build date 2026-11-17

`Max pull`

OD in	Weight lb/ft	Grade	Connection	Body lb	Joint lb	Lesser lb	P_allow lb	Body kN	Joint kN	Lesser kN	P_allow kN
4.5	11.6	C-95	BTC	317,000	325,000	317,000	253,600	1,410.1	1,445.7	1,410.1	1,128.1
4.5	11.6	T-95	LTC	317,000	234,000	234,000	187,200	1,410.1	1,040.9	1,040.9	832.7
4.5	11.6	T-95	BTC	317,000	325,000	317,000	253,600	1,410.1	1,445.7	1,410.1	1,128.1
4.5	11.6	P-110	LTC	367,000	279,000	279,000	223,200	1,632.5	1,241.1	1,241.1	992.8
4.5	11.6	P-110	BTC	367,000	385,000	367,000	293,600	1,632.5	1,712.6	1,632.5	1,306
4.5	13.5	M-65	LTC	249,000	228,000	228,000	182,400	1,107.6	1,014.2	1,014.2	811.4
4.5	13.5	M-65	BTC	249,000	295,000	249,000	199,200	1,107.6	1,312.2	1,107.6	886.1
4.5	13.5	L-80	LTC	307,000	257,000	257,000	205,600	1,365.6	1,143.2	1,143.2	914.6
4.5	13.5	L-80	BTC	307,000	334,000	307,000	245,600	1,365.6	1,485.7	1,365.6	1,092.5
4.5	13.5	N-80	LTC	307,000	270,000	270,000	216,000	1,365.6	1,201	1,201	960.8
4.5	13.5	N-80	BTC	307,000	349,000	307,000	245,600	1,365.6	1,552.4	1,365.6	1,092.5
4.5	13.5	C-90	LTC	345,000	270,000	270,000	216,000	1,534.6	1,201	1,201	960.8
4.5	13.5	C-90	BTC	345,000	355,000	345,000	276,000	1,534.6	1,579.1	1,534.6	1,227.7
4.5	13.5	C-95	LTC	364,000	284,000	284,000	227,200	1,619.2	1,263.3	1,263.3	1,010.6
4.5	13.5	C-95	BTC	364,000	374,000	364,000	291,200	1,619.2	1,663.6	1,619.2	1,295.3
4.5	13.5	T-95	LTC	364,000	284,000	284,000	227,200	1,619.2	1,263.3	1,263.3	1,010.6
4.5	13.5	T-95	BTC	364,000	374,000	364,000	291,200	1,619.2	1,663.6	1,619.2	1,295.3
4.5	13.5	P-110	LTC	422,000	338,000	338,000	270,400	1,877.1	1,503.5	1,503.5	1,202.8
4.5	13.5	P-110	BTC	422,000	443,000	422,000	337,600	1,877.1	1,970.6	1,877.1	1,501.7
4.5	15.1	L-80	LTC	353,000	308,000	308,000	246,400	1,570.2	1,370.1	1,370.1	1,096
4.5	15.1	L-80	BTC	353,000	384,000	353,000	282,400	1,570.2	1,708.1	1,570.2	1,256.2
4.5	15.1	P-110	LTC	485,000	406,000	406,000	324,800	2,157.4	1,806	1,806	1,444.8
4.5	15.1	P-110	BTC	485,000	509,000	485,000	388,000	2,157.4	2,264.1	2,157.4	1,725.9
4.5	15.1	Q-125	LTC	551,000	438,000	438,000	350,400	2,451	1,948.3	1,948.3	1,558.7
4.5	15.1	Q-125	BTC	551,000	554,000	551,000	440,800	2,451	2,464.3	2,451	1,960.8

Check every figure against your own pipe records before you pull.

Casingjacks

Casingjacks LLC | sales@casingjack.com

Max pull tables

Data version 1.326cfcf0 | Build date 2026-11-17

Max pull

OD in	Weight lb/ft	Grade	Connection	Body lb	Joint lb	Lesser lb	P_allow lb	Body kN	Joint kN	Lesser kN	P_allow kN
5	11.5	J-55	STC	182,000	133,000	133,000	106,400	809.6	591.6	591.6	473.3
5	11.5	K-55	STC	182,000	147,000	147,000	117,600	809.6	653.9	653.9	523.1
5	11.5	M-65	STC	215,000	162,000	162,000	129,600	956.4	720.6	720.6	576.5
5	13	J-55	STC	208,000	169,000	169,000	135,200	925.2	751.7	751.7	601.4
5	13	J-55	LTC	208,000	182,000	182,000	145,600	925.2	809.6	809.6	647.7
5	13	J-55	BTC	208,000	252,000	208,000	166,400	925.2	1,121	925.2	740.2
5	13	K-55	STC	208,000	186,000	186,000	148,800	925.2	827.4	827.4	661.9
5	13	K-55	LTC	208,000	201,000	201,000	160,800	925.2	894.1	894.1	715.3
5	13	K-55	BTC	208,000	309,000	208,000	166,400	925.2	1,374.5	925.2	740.2
5	13	M-65	STC	245,000	196,000	196,000	156,800	1,089.8	871.9	871.9	697.5
5	13	M-65	LTC	245,000	212,000	212,000	169,600	1,089.8	943	943	754.4
5	13	M-65	BTC	245,000	288,000	245,000	196,000	1,089.8	1,281.1	1,089.8	871.9
5	15	J-55	STC	241,000	207,000	207,000	165,600	1,072	920.8	920.8	736.6
5	15	J-55	LTC	241,000	223,000	223,000	178,400	1,072	992	992	793.6
5	15	J-55	BTC	241,000	293,000	241,000	192,800	1,072	1,303.3	1,072	857.6
5	15	K-55	STC	241,000	228,000	228,000	182,400	1,072	1,014.2	1,014.2	811.4
5	15	K-55	LTC	241,000	246,000	241,000	192,800	1,072	1,094.3	1,072	857.6
5	15	K-55	BTC	241,000	359,000	241,000	192,800	1,072	1,596.9	1,072	857.6
5	15	M-65	STC	284,000	240,000	240,000	192,000	1,263.3	1,067.6	1,067.6	854.1
5	15	M-65	LTC	284,000	259,000	259,000	207,200	1,263.3	1,152.1	1,152.1	921.7
5	15	M-65	BTC	284,000	334,000	284,000	227,200	1,263.3	1,485.7	1,263.3	1,010.6
5	15	L-80	LTC	350,000	295,000	295,000	236,000	1,556.9	1,312.2	1,312.2	1,049.8
5	15	L-80	BTC	350,000	379,000	350,000	280,000	1,556.9	1,685.9	1,556.9	1,245.5
5	15	N-80	LTC	350,000	311,000	311,000	248,800	1,556.9	1,383.4	1,383.4	1,106.7
5	15	N-80	BTC	350,000	396,000	350,000	280,000	1,556.9	1,761.5	1,556.9	1,245.5

Check every figure against your own pipe records before you pull.

Casingjacks

Casingjacks LLC | sales@casingjack.com

Max pull tables

Data version 1.326cfcf0 | Build date 2026-11-17

Max pull

OD in	Weight lb/ft	Grade	Connection	Body lb	Joint lb	Lesser lb	P_allow lb	Body kN	Joint kN	Lesser kN	P_allow kN
5	15	C-90	LTC	394,000	311,000	311,000	248,800	1,752.6	1,383.4	1,383.4	1,106.7
5	15	C-90	BTC	394,000	404,000	394,000	315,200	1,752.6	1,797.1	1,752.6	1,402.1
5	15	C-95	LTC	416,000	326,000	326,000	260,800	1,850.5	1,450.1	1,450.1	1,160.1
5	15	C-95	BTC	416,000	424,000	416,000	332,800	1,850.5	1,886	1,850.5	1,480.4
5	15	T-95	LTC	416,000	326,000	326,000	260,800	1,850.5	1,450.1	1,450.1	1,160.1
5	15	T-95	BTC	416,000	424,000	416,000	332,800	1,850.5	1,886	1,850.5	1,480.4
5	15	P-110	LTC	481,000	388,000	388,000	310,400	2,139.6	1,725.9	1,725.9	1,380.7
5	15	P-110	BTC	481,000	503,000	481,000	384,800	2,139.6	2,237.5	2,139.6	1,711.7
5	18	M-65	LTC	343,000	331,000	331,000	264,800	1,525.7	1,472.4	1,472.4	1,177.9
5	18	M-65	BTC	343,000	403,000	343,000	274,400	1,525.7	1,792.6	1,525.7	1,220.6
5	18	L-80	LTC	422,000	377,000	377,000	301,600	1,877.1	1,677	1,677	1,341.6
5	18	L-80	BTC	422,000	457,000	422,000	337,600	1,877.1	2,032.8	1,877.1	1,501.7
5	18	N-80	LTC	422,000	396,000	396,000	316,800	1,877.1	1,761.5	1,761.5	1,409.2
5	18	N-80	BTC	422,000	477,000	422,000	337,600	1,877.1	2,121.8	1,877.1	1,501.7
5	18	C-90	LTC	475,000	396,000	396,000	316,800	2,112.9	1,761.5	1,761.5	1,409.2
5	18	C-90	BTC	475,000	484,000	475,000	380,000	2,112.9	2,152.9	2,112.9	1,690.3
5	18	C-95	LTC	501,000	416,000	416,000	332,800	2,228.6	1,850.5	1,850.5	1,480.4
5	18	C-95	BTC	501,000	512,000	501,000	400,800	2,228.6	2,277.5	2,228.6	1,782.8
5	18	T-95	LTC	501,000	416,000	416,000	332,800	2,228.6	1,850.5	1,850.5	1,480.4
5	18	T-95	BTC	501,000	512,000	501,000	400,800	2,228.6	2,277.5	2,228.6	1,782.8
5	18	P-110	LTC	580,000	495,000	495,000	396,000	2,580	2,201.9	2,201.9	1,761.5
5	18	P-110	BTC	580,000	606,000	580,000	464,000	2,580	2,695.6	2,580	2,064
5	18	Q-125	LTC	659,000	535,000	535,000	428,000	2,931.4	2,379.8	2,379.8	1,903.8
5	18	Q-125	BTC	659,000	661,000	659,000	527,200	2,931.4	2,940.3	2,931.4	2,345.1
5	21.4	L-80	LTC	501,000	466,000	466,000	372,800	2,228.6	2,072.9	2,072.9	1,658.3

Check every figure against your own pipe records before you pull.

Casingjacks

Casingjacks LLC | sales@casingjack.com

Max pull tables

Data version 1.326cfcf0 | Build date 2026-11-17

Max pull

OD in	Weight lb/ft	Grade	Connection	Body lb	Joint lb	Lesser lb	P_allow lb	Body kN	Joint kN	Lesser kN	P_allow kN
5	21.4	L-80	BTC	501,000	510,000	501,000	400,800	2,228.6	2,268.6	2,228.6	1,782.8
5	21.4	N-80	LTC	501,000	490,000	490,000	392,000	2,228.6	2,179.6	2,179.6	1,743.7
5	21.4	N-80	BTC	501,000	537,000	501,000	400,800	2,228.6	2,388.7	2,228.6	1,782.8
5	21.4	C-90	LTC	564,000	490,000	490,000	392,000	2,508.8	2,179.6	2,179.6	1,743.7
5	21.4	C-90	BTC	564,000	537,000	537,000	429,600	2,508.8	2,388.7	2,388.7	1,911
5	21.4	C-95	LTC	595,000	515,000	515,000	412,000	2,646.7	2,290.8	2,290.8	1,832.7
5	21.4	C-95	BTC	595,000	563,000	563,000	450,400	2,646.7	2,504.3	2,504.3	2,003.5
5	21.4	T-95	LTC	595,000	515,000	515,000	412,000	2,646.7	2,290.8	2,290.8	1,832.7
5	21.4	T-95	BTC	595,000	563,000	563,000	450,400	2,646.7	2,504.3	2,504.3	2,003.5
5	21.4	P-110	LTC	689,000	613,000	613,000	490,400	3,064.8	2,726.8	2,726.8	2,181.4
5	21.4	P-110	BTC	689,000	671,000	671,000	536,800	3,064.8	2,984.8	2,984.8	2,387.8
5	21.4	Q-125	LTC	783,000	662,000	662,000	529,600	3,483	2,944.7	2,944.7	2,355.8
5	21.4	Q-125	BTC	783,000	724,000	724,000	579,200	3,483	3,220.5	3,220.5	2,576.4
5	23.2	L-80	LTC	543,000	513,000	513,000	410,400	2,415.4	2,281.9	2,281.9	1,825.6
5	23.2	L-80	BTC	543,000	510,000	510,000	408,000	2,415.4	2,268.6	2,268.6	1,814.9
5	23.2	N-80	LTC	543,000	540,000	540,000	432,000	2,415.4	2,402	2,402	1,921.6
5	23.2	N-80	BTC	543,000	537,000	537,000	429,600	2,415.4	2,388.7	2,388.7	1,911
5	23.2	C-90	LTC	611,000	540,000	540,000	432,000	2,717.9	2,402	2,402	1,921.6
5	23.2	C-90	BTC	611,000	537,000	537,000	429,600	2,717.9	2,388.7	2,388.7	1,911
5	23.2	C-95	LTC	645,000	567,000	567,000	453,600	2,869.1	2,522.1	2,522.1	2,017.7
5	23.2	C-95	BTC	645,000	563,000	563,000	450,400	2,869.1	2,504.3	2,504.3	2,003.5
5	23.2	T-95	LTC	645,000	567,000	567,000	453,600	2,869.1	2,522.1	2,522.1	2,017.7
5	23.2	T-95	BTC	645,000	563,000	563,000	450,400	2,869.1	2,504.3	2,504.3	2,003.5
5	23.2	P-110	LTC	747,000	675,000	675,000	540,000	3,322.8	3,002.5	3,002.5	2,402
5	23.2	P-110	BTC	747,000	671,000	671,000	536,800	3,322.8	2,984.8	2,984.8	2,387.8

Check every figure against your own pipe records before you pull.

Casingjacks

Casingjacks LLC | sales@casingjack.com

Max pull tables

Data version 1.326cfcf0 | Build date 2026-11-17

`Max pull`

OD in	Weight lb/ft	Grade	Connection	Body lb	Joint lb	Lesser lb	P_allow lb	Body kN	Joint kN	Lesser kN	P_allow kN
5	23.2	Q-125	LTC	849,000	729,000	729,000	583,200	3,776.5	3,242.8	3,242.8	2,594.2
5	23.2	Q-125	BTC	849,000	724,000	724,000	579,200	3,776.5	3,220.5	3,220.5	2,576.4
5	24.1	L-80	LTC	566,000	538,000	538,000	430,400	2,517.7	2,393.1	2,393.1	1,914.5
5	24.1	L-80	BTC	566,000	510,000	510,000	408,000	2,517.7	2,268.6	2,268.6	1,814.9
5	24.1	N-80	LTC	566,000	558,000	558,000	446,400	2,517.7	2,482.1	2,482.1	1,985.7
5	24.1	N-80	BTC	566,000	537,000	537,000	429,600	2,517.7	2,388.7	2,388.7	1,911
5	24.1	C-90	LTC	636,000	567,000	567,000	453,600	2,829.1	2,522.1	2,522.1	2,017.7
5	24.1	C-90	BTC	636,000	537,000	537,000	429,600	2,829.1	2,388.7	2,388.7	1,911
5	24.1	C-95	LTC	672,000	595,000	595,000	476,000	2,989.2	2,646.7	2,646.7	2,117.4
5	24.1	C-95	BTC	672,000	563,000	563,000	450,400	2,989.2	2,504.3	2,504.3	2,003.5
5	24.1	T-95	LTC	672,000	595,000	595,000	476,000	2,989.2	2,646.7	2,646.7	2,117.4
5	24.1	T-95	BTC	672,000	563,000	563,000	450,400	2,989.2	2,504.3	2,504.3	2,003.5
5	24.1	P-110	LTC	778,000	708,000	708,000	566,400	3,460.7	3,149.3	3,149.3	2,519.5
5	24.1	P-110	BTC	778,000	671,000	671,000	536,800	3,460.7	2,984.8	2,984.8	2,387.8
5	24.1	Q-125	LTC	884,000	765,000	765,000	612,000	3,932.2	3,402.9	3,402.9	2,722.3
5	24.1	Q-125	BTC	884,000	724,000	724,000	579,200	3,932.2	3,220.5	3,220.5	2,576.4
5.5	15.5	J-55	STC	248,000	202,000	202,000	161,600	1,103.2	898.5	898.5	718.8
5.5	15.5	J-55	LTC	248,000	217,000	217,000	173,600	1,103.2	965.3	965.3	772.2
5.5	15.5	J-55	BTC	248,000	300,000	248,000	198,400	1,103.2	1,334.5	1,103.2	882.5
5.5	15.5	K-55	STC	248,000	222,000	222,000	177,600	1,103.2	987.5	987.5	790
5.5	15.5	K-55	LTC	248,000	239,000	239,000	191,200	1,103.2	1,063.1	1,063.1	850.5
5.5	15.5	K-55	BTC	248,000	366,000	248,000	198,400	1,103.2	1,628	1,103.2	882.5
5.5	15.5	M-65	STC	293,000	235,000	235,000	188,000	1,303.3	1,045.3	1,045.3	836.3
5.5	15.5	M-65	LTC	293,000	253,000	253,000	202,400	1,303.3	1,125.4	1,125.4	900.3
5.5	15.5	M-65	BTC	293,000	342,000	293,000	234,400	1,303.3	1,521.3	1,303.3	1,042.7

Check every figure against your own pipe records before you pull.

Casingjacks

Casingjacks LLC | sales@casingjack.com

Max pull tables

Data version 1.326cfcf0 | Build date 2026-11-17

Max pull

OD in	Weight lb/ft	Grade	Connection	Body lb	Joint lb	Lesser lb	P_allow lb	Body kN	Joint kN	Lesser kN	P_allow kN
5.5	17	J-55	STC	273,000	229,000	229,000	183,200	1,214.4	1,018.6	1,018.6	814.9
5.5	17	J-55	LTC	273,000	247,000	247,000	197,600	1,214.4	1,098.7	1,098.7	879
5.5	17	J-55	BTC	273,000	329,000	273,000	218,400	1,214.4	1,463.5	1,214.4	971.5
5.5	17	K-55	STC	273,000	252,000	252,000	201,600	1,214.4	1,121	1,121	896.8
5.5	17	K-55	LTC	273,000	272,000	272,000	217,600	1,214.4	1,209.9	1,209.9	967.9
5.5	17	K-55	BTC	273,000	402,000	273,000	218,400	1,214.4	1,788.2	1,214.4	971.5
5.5	17	M-65	STC	323,000	267,000	267,000	213,600	1,436.8	1,187.7	1,187.7	950.1
5.5	17	M-65	LTC	323,000	287,000	287,000	229,600	1,436.8	1,276.6	1,276.6	1,021.3
5.5	17	M-65	BTC	323,000	376,000	323,000	258,400	1,436.8	1,672.5	1,436.8	1,149.4
5.5	17	L-80	LTC	397,000	338,000	338,000	270,400	1,765.9	1,503.5	1,503.5	1,202.8
5.5	17	L-80	BTC	397,000	428,000	397,000	317,600	1,765.9	1,903.8	1,765.9	1,412.8
5.5	17	N-80	LTC	397,000	348,000	348,000	278,400	1,765.9	1,548	1,548	1,238.4
5.5	17	N-80	BTC	397,000	446,000	397,000	317,600	1,765.9	1,983.9	1,765.9	1,412.8
5.5	17	C-90	LTC	447,000	356,000	356,000	284,800	1,988.4	1,583.6	1,583.6	1,266.9
5.5	17	C-90	BTC	447,000	456,000	447,000	357,600	1,988.4	2,028.4	1,988.4	1,590.7
5.5	17	C-95	LTC	471,000	374,000	374,000	299,200	2,095.1	1,663.6	1,663.6	1,330.9
5.5	17	C-95	BTC	471,000	480,000	471,000	376,800	2,095.1	2,135.1	2,095.1	1,676.1
5.5	17	T-95	LTC	471,000	374,000	374,000	299,200	2,095.1	1,663.6	1,663.6	1,330.9
5.5	17	T-95	BTC	471,000	480,000	471,000	376,800	2,095.1	2,135.1	2,095.1	1,676.1
5.5	17	P-110	LTC	546,000	445,000	445,000	356,000	2,428.7	1,979.5	1,979.5	1,583.6
5.5	17	P-110	BTC	546,000	568,000	546,000	436,800	2,428.7	2,526.6	2,428.7	1,943
5.5	17	Q-125	LTC	620,000	481,000	481,000	384,800	2,757.9	2,139.6	2,139.6	1,711.7
5.5	17	Q-125	BTC	620,000	620,000	620,000	496,000	2,757.9	2,757.9	2,757.9	2,206.3
5.5	20	M-65	LTC	379,000	353,000	353,000	282,400	1,685.9	1,570.2	1,570.2	1,256.2
5.5	20	M-65	BTC	379,000	442,000	379,000	303,200	1,685.9	1,966.1	1,685.9	1,348.7

Check every figure against your own pipe records before you pull.

Casingjacks

Casingjacks LLC | sales@casingjack.com

Max pull tables

Data version 1.326cfcf0 | Build date 2026-11-17

`Max pull`

OD in	Weight lb/ft	Grade	Connection	Body lb	Joint lb	Lesser lb	P_allow lb	Body kN	Joint kN	Lesser kN	P_allow kN
5.5	20	L-80	LTC	466,000	416,000	416,000	332,800	2,072.9	1,850.5	1,850.5	1,480.4
5.5	20	L-80	BTC	466,000	503,000	466,000	372,800	2,072.9	2,237.5	2,072.9	1,658.3
5.5	20	N-80	LTC	466,000	428,000	428,000	342,400	2,072.9	1,903.8	1,903.8	1,523.1
5.5	20	N-80	BTC	466,000	524,000	466,000	372,800	2,072.9	2,330.9	2,072.9	1,658.3
5.5	20	C-90	LTC	525,000	438,000	438,000	350,400	2,335.3	1,948.3	1,948.3	1,558.7
5.5	20	C-90	BTC	525,000	436,000	436,000	348,800	2,335.3	1,939.4	1,939.4	1,551.5
5.5	20	C-95	LTC	554,000	460,000	460,000	368,000	2,464.3	2,046.2	2,046.2	1,636.9
5.5	20	C-95	BTC	554,000	563,000	554,000	443,200	2,464.3	2,504.3	2,464.3	1,971.5
5.5	20	T-95	LTC	554,000	460,000	460,000	368,000	2,464.3	2,046.2	2,046.2	1,636.9
5.5	20	T-95	BTC	554,000	563,000	554,000	443,200	2,464.3	2,504.3	2,464.3	1,971.5
5.5	20	P-110	LTC	641,000	548,000	548,000	438,400	2,851.3	2,437.6	2,437.6	1,950.1
5.5	20	P-110	BTC	641,000	667,000	641,000	512,800	2,851.3	2,967	2,851.3	2,281
5.5	20	Q-125	LTC	729,000	592,000	592,000	473,600	3,242.8	2,633.3	2,633.3	2,106.7
5.5	20	Q-125	BTC	729,000	728,000	728,000	582,400	3,242.8	3,238.3	3,238.3	2,590.6
5.5	23	L-80	LTC	530,000	489,000	489,000	391,200	2,357.6	2,175.2	2,175.2	1,740.1
5.5	23	L-80	BTC	530,000	550,000	530,000	424,000	2,357.6	2,446.5	2,357.6	1,886
5.5	23	N-80	LTC	530,000	502,000	502,000	401,600	2,357.6	2,233	2,233	1,786.4
5.5	23	N-80	BTC	530,000	579,000	530,000	424,000	2,357.6	2,575.5	2,357.6	1,886
5.5	23	C-90	LTC	597,000	514,000	514,000	411,200	2,655.6	2,286.4	2,286.4	1,829.1
5.5	23	C-90	BTC	597,000	579,000	579,000	463,200	2,655.6	2,575.5	2,575.5	2,060.4
5.5	23	C-95	LTC	630,000	540,000	540,000	432,000	2,802.4	2,402	2,402	1,921.6
5.5	23	C-95	BTC	630,000	608,000	608,000	486,400	2,802.4	2,704.5	2,704.5	2,163.6
5.5	23	T-95	LTC	630,000	540,000	540,000	432,000	2,802.4	2,402	2,402	1,921.6
5.5	23	T-95	BTC	630,000	608,000	608,000	486,400	2,802.4	2,704.5	2,704.5	2,163.6
5.5	23	P-110	LTC	729,000	643,000	643,000	514,400	3,242.8	2,860.2	2,860.2	2,288.2

Check every figure against your own pipe records before you pull.

Casingjacks

Casingjacks LLC | sales@casingjack.com

Max pull tables

Data version 1.326cfcf0 | Build date 2026-11-17

Max pull

OD in	Weight lb/ft	Grade	Connection	Body lb	Joint lb	Lesser lb	P_allow lb	Body kN	Joint kN	Lesser kN	P_allow kN
5.5	23	P-110	BTC	729,000	724,000	724,000	579,200	3,242.8	3,220.5	3,220.5	2,576.4
5.5	23	Q-125	LTC	829,000	694,000	694,000	555,200	3,687.6	3,087.1	3,087.1	2,469.7
5.5	23	Q-125	BTC	829,000	782,000	782,000	625,600	3,687.6	3,478.5	3,478.5	2,782.8
5.5	26	C-90	LTC	676,000	598,000	598,000	478,400	3,007	2,660	2,660	2,128
5.5	26	C-90	BTC	676,000	579,000	579,000	463,200	3,007	2,575.5	2,575.5	2,060.4
5.5	26	C-95	LTC	714,000	628,000	628,000	502,400	3,176	2,793.5	2,793.5	2,234.8
5.5	26	C-95	BTC	714,000	608,000	608,000	486,400	3,176	2,704.5	2,704.5	2,163.6
5.5	26	T-95	LTC	714,000	628,000	628,000	502,400	3,176	2,793.5	2,793.5	2,234.8
5.5	26	T-95	BTC	714,000	608,000	608,000	486,400	3,176	2,704.5	2,704.5	2,163.6
5.5	26	P-110	LTC	826,000	748,000	748,000	598,400	3,674.2	3,327.3	3,327.3	2,661.8
5.5	26	P-110	BTC	826,000	724,000	724,000	579,200	3,674.2	3,220.5	3,220.5	2,576.4
5.5	26	Q-125	LTC	939,000	808,000	808,000	646,400	4,176.9	3,594.2	3,594.2	2,875.3
5.5	26	Q-125	BTC	939,000	782,000	782,000	625,600	4,176.9	3,478.5	3,478.5	2,782.8
5.5	26.8	C-90	Body only	707,000	Not recorded	707,000	565,600	3,144.9	Not recorded	3,144.9	2,515.9
5.5	26.8	T-95	Body only	746,000	Not recorded	746,000	596,800	3,318.4	Not recorded	3,318.4	2,654.7
5.5	29.7	C-90	Body only	785,000	Not recorded	785,000	628,000	3,491.9	Not recorded	3,491.9	2,793.5
5.5	29.7	T-95	Body only	828,000	Not recorded	828,000	662,400	3,683.1	Not recorded	3,683.1	2,946.5
5.5	32.6	C-90	Body only	861,000	Not recorded	861,000	688,800	3,829.9	Not recorded	3,829.9	3,063.9
5.5	32.6	T-95	Body only	909,000	Not recorded	909,000	727,200	4,043.4	Not recorded	4,043.4	3,234.7
5.5	35.3	C-90	Body only	935,000	Not recorded	935,000	748,000	4,159.1	Not recorded	4,159.1	3,327.3
5.5	35.3	T-95	Body only	987,000	Not recorded	987,000	789,600	4,390.4	Not recorded	4,390.4	3,512.3
5.5	38	C-90	Body only	1,007,000	Not recorded	1,007,000	805,600	4,479.4	Not recorded	4,479.4	3,583.5
5.5	38	T-95	Body only	1,063,000	Not recorded	1,063,000	850,400	4,728.5	Not recorded	4,728.5	3,782.8
5.5	40.5	C-90	Body only	1,076,000	Not recorded	1,076,000	860,800	4,786.3	Not recorded	4,786.3	3,829
5.5	40.5	T-95	Body only	1,136,000	Not recorded	1,136,000	908,800	5,053.2	Not recorded	5,053.2	4,042.5

Check every figure against your own pipe records before you pull.

Casingjacks

Casingjacks LLC | sales@casingjack.com

Max pull tables

Data version 1.326cfcf0 | Build date 2026-11-17

Max pull

OD in	Weight lb/ft	Grade	Connection	Body lb	Joint lb	Lesser lb	P_allow lb	Body kN	Joint kN	Lesser kN	P_allow kN
5.5	43.1	C-90	Body only	1,144,000	Not recorded	1,144,000	915,200	5,088.8	Not recorded	5,088.8	4,071
5.5	43.1	T-95	Body only	1,208,000	Not recorded	1,208,000	966,400	5,373.5	Not recorded	5,373.5	4,298.8
5.625	26.7	L-80	LTC	617,000	488,000	488,000	390,400	2,744.6	2,170.7	2,170.7	1,736.6
5.625	26.7	L-80	BTC	617,000	550,000	550,000	440,000	2,744.6	2,446.5	2,446.5	1,957.2
5.625	26.7	P-110	LTC	849,000	642,000	642,000	513,600	3,776.5	2,855.8	2,855.8	2,284.6
5.625	26.7	P-110	BTC	849,000	724,000	724,000	579,200	3,776.5	3,220.5	3,220.5	2,576.4
5.75	18.1	J-55	BTC	286,000	344,000	286,000	228,800	1,272.2	1,530.2	1,272.2	1,017.8
5.75	18.1	L-80	BTC	416,000	447,000	416,000	332,800	1,850.5	1,988.4	1,850.5	1,480.4
5.75	18.1	N-80	BTC	416,000	466,000	416,000	332,800	1,850.5	2,072.9	1,850.5	1,480.4
5.75	18.1	P-110	BTC	572,000	594,000	572,000	457,600	2,544.4	2,642.2	2,544.4	2,035.5
5.75	19.7	J-55	BTC	313,000	377,000	313,000	250,400	1,392.3	1,677	1,392.3	1,113.8
5.75	19.7	L-80	BTC	456,000	490,000	456,000	364,800	2,028.4	2,179.6	2,028.4	1,622.7
5.75	19.7	N-80	BTC	456,000	511,000	456,000	364,800	2,028.4	2,273	2,028.4	1,622.7
5.75	19.7	P-110	BTC	627,000	651,000	627,000	501,600	2,789	2,895.8	2,789	2,231.2
5.75	21.8	L-80	BTC	507,000	545,000	507,000	405,600	2,255.2	2,424.3	2,255.2	1,804.2
5.75	21.8	N-80	BTC	507,000	568,000	507,000	405,600	2,255.2	2,526.6	2,255.2	1,804.2
5.75	21.8	P-110	BTC	697,000	723,000	697,000	557,600	3,100.4	3,216.1	3,100.4	2,480.3
5.75	24.2	L-80	BTC	563,000	605,000	563,000	450,400	2,504.3	2,691.2	2,504.3	2,003.5
5.75	24.2	N-80	BTC	563,000	630,000	563,000	450,400	2,504.3	2,802.4	2,504.3	2,003.5
5.75	24.2	P-110	BTC	774,000	803,000	774,000	619,200	3,442.9	3,571.9	3,442.9	2,754.3
6.625	20	H-40	STC	229,000	184,000	184,000	147,200	1,018.6	818.5	818.5	654.8
6.625	20	J-55	STC	315,000	245,000	245,000	196,000	1,401.2	1,089.8	1,089.8	871.9
6.625	20	J-55	LTC	315,000	266,000	266,000	212,800	1,401.2	1,183.2	1,183.2	946.6
6.625	20	J-55	BTC	315,000	374,000	315,000	252,000	1,401.2	1,663.6	1,401.2	1,121
6.625	20	K-55	STC	315,000	267,000	267,000	213,600	1,401.2	1,187.7	1,187.7	950.1

Check every figure against your own pipe records before you pull.

Casingjacks

Casingjacks LLC | sales@casingjack.com

Max pull tables

Data version 1.326cfcf0 | Build date 2026-11-17

Max pull

OD in	Weight lb/ft	Grade	Connection	Body lb	Joint lb	Lesser lb	P_allow lb	Body kN	Joint kN	Lesser kN	P_allow kN
6.625	20	K-55	LTC	315,000	290,000	290,000	232,000	1,401.2	1,290	1,290	1,032
6.625	20	K-55	BTC	315,000	453,000	315,000	252,000	1,401.2	2,015	1,401.2	1,121
6.625	20	M-65	STC	373,000	285,000	285,000	228,000	1,659.2	1,267.7	1,267.7	1,014.2
6.625	20	M-65	LTC	373,000	309,000	309,000	247,200	1,659.2	1,374.5	1,374.5	1,099.6
6.625	20	M-65	BTC	373,000	428,000	373,000	298,400	1,659.2	1,903.8	1,659.2	1,327.3
6.625	24	J-55	STC	382,000	314,000	314,000	251,200	1,699.2	1,396.7	1,396.7	1,117.4
6.625	24	J-55	LTC	382,000	340,000	340,000	272,000	1,699.2	1,512.4	1,512.4	1,209.9
6.625	24	J-55	BTC	382,000	453,000	382,000	305,600	1,699.2	2,015	1,699.2	1,359.4
6.625	24	K-55	STC	382,000	342,000	342,000	273,600	1,699.2	1,521.3	1,521.3	1,217
6.625	24	K-55	LTC	382,000	372,000	372,000	297,600	1,699.2	1,654.7	1,654.7	1,323.8
6.625	24	K-55	BTC	382,000	548,000	382,000	305,600	1,699.2	2,437.6	1,699.2	1,359.4
6.625	24	M-65	STC	451,000	366,000	366,000	292,800	2,006.1	1,628	1,628	1,302.4
6.625	24	M-65	LTC	451,000	397,000	397,000	317,600	2,006.1	1,765.9	1,765.9	1,412.8
6.625	24	M-65	BTC	451,000	518,000	451,000	360,800	2,006.1	2,304.2	2,006.1	1,604.9
6.625	24	L-80	LTC	555,000	473,000	473,000	378,400	2,468.8	2,104	2,104	1,683.2
6.625	24	L-80	BTC	555,000	592,000	555,000	444,000	2,468.8	2,633.3	2,468.8	1,975
6.625	24	C-90	LTC	624,000	520,000	520,000	416,000	2,775.7	2,313.1	2,313.1	1,850.5
6.625	24	C-90	BTC	624,000	633,000	624,000	499,200	2,775.7	2,815.7	2,775.7	2,220.6
6.625	24	C-95	LTC	659,000	546,000	546,000	436,800	2,931.4	2,428.7	2,428.7	1,943
6.625	24	C-95	BTC	659,000	665,000	659,000	527,200	2,931.4	2,958.1	2,931.4	2,345.1
6.625	24	P-110	LTC	763,000	641,000	641,000	512,800	3,394	2,851.3	2,851.3	2,281
6.625	24	P-110	BTC	763,000	786,000	763,000	610,400	3,394	3,496.3	3,394	2,715.2
6.625	28	M-65	LTC	529,000	483,000	483,000	386,400	2,353.1	2,148.5	2,148.5	1,718.8
6.625	28	M-65	BTC	529,000	607,000	529,000	423,200	2,353.1	2,700.1	2,353.1	1,882.5
6.625	28	L-80	LTC	651,000	576,000	576,000	460,800	2,895.8	2,562.2	2,562.2	2,049.7

Check every figure against your own pipe records before you pull.

Casingjacks

Casingjacks LLC | sales@casingjack.com

Max pull tables

Data version 1.326cfcf0 | Build date 2026-11-17

`Max pull`

OD in	Weight lb/ft	Grade	Connection	Body lb	Joint lb	Lesser lb	P_allow lb	Body kN	Joint kN	Lesser kN	P_allow kN
6.625	28	L-80	BTC	651,000	693,000	651,000	520,800	2,895.8	3,082.6	2,895.8	2,316.6
6.625	28	N-80	LTC	651,000	586,000	586,000	468,800	2,895.8	2,606.7	2,606.7	2,085.3
6.625	28	N-80	BTC	651,000	721,000	651,000	520,800	2,895.8	3,207.2	2,895.8	2,316.6
6.625	28	C-90	LTC	732,000	633,000	633,000	506,400	3,256.1	2,815.7	2,815.7	2,252.6
6.625	28	C-90	BTC	732,000	742,000	732,000	585,600	3,256.1	3,300.6	3,256.1	2,604.9
6.625	28	C-95	LTC	773,000	665,000	665,000	532,000	3,438.5	2,958.1	2,958.1	2,366.5
6.625	28	C-95	BTC	773,000	780,000	773,000	618,400	3,438.5	3,469.6	3,438.5	2,750.8
6.625	28	P-110	LTC	895,000	781,000	781,000	624,800	3,981.2	3,474.1	3,474.1	2,779.2
6.625	28	P-110	BTC	895,000	922,000	895,000	716,000	3,981.2	4,101.3	3,981.2	3,184.9
6.625	32	L-80	LTC	734,000	666,000	666,000	532,800	3,265	2,962.5	2,962.5	2,370
6.625	32	L-80	BTC	734,000	783,000	734,000	587,200	3,265	3,483	3,265	2,612
6.625	32	N-80	LTC	734,000	677,000	677,000	541,600	3,265	3,011.4	3,011.4	2,409.2
6.625	32	N-80	BTC	734,000	814,000	734,000	587,200	3,265	3,620.9	3,265	2,612
6.625	32	C-90	LTC	826,000	732,000	732,000	585,600	3,674.2	3,256.1	3,256.1	2,604.9
6.625	32	C-90	BTC	826,000	837,000	826,000	660,800	3,674.2	3,723.2	3,674.2	2,939.4
6.625	32	C-95	LTC	872,000	769,000	769,000	615,200	3,878.8	3,420.7	3,420.7	2,736.5
6.625	32	C-95	BTC	872,000	880,000	872,000	697,600	3,878.8	3,914.4	3,878.8	3,103.1
6.625	32	P-110	LTC	1,009,000	904,000	904,000	723,200	4,488.3	4,021.2	4,021.2	3,217
6.625	32	P-110	BTC	1,009,000	1,040,000	1,009,000	807,200	4,488.3	4,626.2	4,488.3	3,590.6
6.625	32	Q-125	LTC	1,147,000	989,000	989,000	791,200	5,102.1	4,399.3	4,399.3	3,519.4
6.625	32	Q-125	BTC	1,147,000	1,138,000	1,138,000	910,400	5,102.1	5,062.1	5,062.1	4,049.7
7	20	H-40	STC	230,000	176,000	176,000	140,800	1,023.1	782.9	782.9	626.3
7	20	J-55	STC	316,000	234,000	234,000	187,200	1,405.6	1,040.9	1,040.9	832.7
7	20	J-55	LTC	316,000	257,000	257,000	205,600	1,405.6	1,143.2	1,143.2	914.6
7	20	J-55	BTC	316,000	373,000	316,000	252,800	1,405.6	1,659.2	1,405.6	1,124.5

Check every figure against your own pipe records before you pull.

Casingjacks

Casingjacks LLC | sales@casingjack.com

Max pull tables

Data version 1.326cfcf0 | Build date 2026-11-17

Max pull

OD in	Weight lb/ft	Grade	Connection	Body lb	Joint lb	Lesser lb	P_allow lb	Body kN	Joint kN	Lesser kN	P_allow kN
7	20	K-55	STC	316,000	254,000	254,000	203,200	1,405.6	1,129.8	1,129.8	903.9
7	20	K-55	LTC	316,000	281,000	281,000	224,800	1,405.6	1,250	1,250	1,000
7	20	K-55	BTC	316,000	451,000	316,000	252,800	1,405.6	2,006.1	1,405.6	1,124.5
7	20	M-65	STC	374,000	272,000	272,000	217,600	1,663.6	1,209.9	1,209.9	967.9
7	20	M-65	LTC	374,000	300,000	300,000	240,000	1,663.6	1,334.5	1,334.5	1,067.6
7	20	M-65	BTC	374,000	427,000	374,000	299,200	1,663.6	1,899.4	1,663.6	1,330.9
7	23	J-55	STC	366,000	284,000	284,000	227,200	1,628	1,263.3	1,263.3	1,010.6
7	23	J-55	LTC	366,000	313,000	313,000	250,400	1,628	1,392.3	1,392.3	1,113.8
7	23	J-55	BTC	366,000	432,000	366,000	292,800	1,628	1,921.6	1,628	1,302.4
7	23	K-55	STC	366,000	309,000	309,000	247,200	1,628	1,374.5	1,374.5	1,099.6
7	23	K-55	LTC	366,000	341,000	341,000	272,800	1,628	1,516.8	1,516.8	1,213.5
7	23	K-55	BTC	366,000	522,000	366,000	292,800	1,628	2,322	1,628	1,302.4
7	23	M-65	STC	433,000	331,000	331,000	264,800	1,926.1	1,472.4	1,472.4	1,177.9
7	23	M-65	LTC	433,000	364,000	364,000	291,200	1,926.1	1,619.2	1,619.2	1,295.3
7	23	M-65	BTC	433,000	494,000	433,000	346,400	1,926.1	2,197.4	1,926.1	1,540.9
7	23	L-80	LTC	532,000	435,000	435,000	348,000	2,366.5	1,935	1,935	1,548
7	23	L-80	BTC	532,000	565,000	532,000	425,600	2,366.5	2,513.2	2,366.5	1,893.2
7	23	N-80	LTC	532,000	442,000	442,000	353,600	2,366.5	1,966.1	1,966.1	1,572.9
7	23	N-80	BTC	532,000	588,000	532,000	425,600	2,366.5	2,615.6	2,366.5	1,893.2
7	23	C-90	LTC	599,000	479,000	479,000	383,200	2,664.5	2,130.7	2,130.7	1,704.6
7	23	C-90	BTC	599,000	605,000	599,000	479,200	2,664.5	2,691.2	2,664.5	2,131.6
7	23	C-95	LTC	632,000	505,000	505,000	404,000	2,811.3	2,246.4	2,246.4	1,797.1
7	23	C-95	BTC	632,000	636,000	632,000	505,600	2,811.3	2,829.1	2,811.3	2,249
7	23	T-95	LTC	632,000	505,000	505,000	404,000	2,811.3	2,246.4	2,246.4	1,797.1
7	23	T-95	BTC	632,000	636,000	632,000	505,600	2,811.3	2,829.1	2,811.3	2,249

Check every figure against your own pipe records before you pull.

Casingjacks

Casingjacks LLC | sales@casingjack.com

Max pull tables

Data version 1.326cfcf0 | Build date 2026-11-17

Max pull

OD in	Weight lb/ft	Grade	Connection	Body lb	Joint lb	Lesser lb	P_allow lb	Body kN	Joint kN	Lesser kN	P_allow kN
7	26	J-55	STC	415,000	334,000	334,000	267,200	1,846	1,485.7	1,485.7	1,188.6
7	26	J-55	LTC	415,000	367,000	367,000	293,600	1,846	1,632.5	1,632.5	1,306
7	26	J-55	BTC	415,000	490,000	415,000	332,000	1,846	2,179.6	1,846	1,476.8
7	26	K-55	STC	415,000	364,000	364,000	291,200	1,846	1,619.2	1,619.2	1,295.3
7	26	K-55	LTC	415,000	401,000	401,000	320,800	1,846	1,783.7	1,783.7	1,427
7	26	K-55	BTC	415,000	592,000	415,000	332,000	1,846	2,633.3	1,846	1,476.8
7	26	M-65	STC	491,000	389,000	389,000	311,200	2,184.1	1,730.4	1,730.4	1,384.3
7	26	M-65	LTC	491,000	428,000	428,000	342,400	2,184.1	1,903.8	1,903.8	1,523.1
7	26	M-65	BTC	491,000	561,000	491,000	392,800	2,184.1	2,495.5	2,184.1	1,747.3
7	26	L-80	LTC	604,000	511,000	511,000	408,800	2,686.7	2,273	2,273	1,818.4
7	26	L-80	BTC	604,000	641,000	604,000	483,200	2,686.7	2,851.3	2,686.7	2,149.4
7	26	N-80	LTC	604,000	519,000	519,000	415,200	2,686.7	2,308.6	2,308.6	1,846.9
7	26	N-80	BTC	604,000	667,000	604,000	483,200	2,686.7	2,967	2,686.7	2,149.4
7	26	C-90	LTC	679,000	563,000	563,000	450,400	3,020.3	2,504.3	2,504.3	2,003.5
7	26	C-90	BTC	679,000	687,000	679,000	543,200	3,020.3	3,055.9	3,020.3	2,416.3
7	26	C-95	LTC	717,000	593,000	593,000	474,400	3,189.4	2,637.8	2,637.8	2,110.2
7	26	C-95	BTC	717,000	722,000	717,000	573,600	3,189.4	3,211.6	3,189.4	2,551.5
7	26	T-95	LTC	717,000	593,000	593,000	474,400	3,189.4	2,637.8	2,637.8	2,110.2
7	26	T-95	BTC	717,000	722,000	717,000	573,600	3,189.4	3,211.6	3,189.4	2,551.5
7	26	P-110	LTC	830,000	639,000	639,000	511,200	3,692	2,842.4	2,842.4	2,273.9
7	26	P-110	BTC	830,000	853,000	830,000	664,000	3,692	3,794.3	3,692	2,953.6
7	29	M-65	LTC	549,000	492,000	492,000	393,600	2,442.1	2,188.5	2,188.5	1,750.8
7	29	M-65	BTC	549,000	628,000	549,000	439,200	2,442.1	2,793.5	2,442.1	1,953.7
7	29	L-80	LTC	676,000	587,000	587,000	469,600	3,007	2,611.1	2,611.1	2,088.9
7	29	L-80	BTC	676,000	718,000	676,000	540,800	3,007	3,193.8	3,007	2,405.6

Check every figure against your own pipe records before you pull.

Casingjacks

Casingjacks LLC | sales@casingjack.com

Max pull tables

Data version 1.326cfcf0 | Build date 2026-11-17

Max pull

OD in	Weight lb/ft	Grade	Connection	Body lb	Joint lb	Lesser lb	P_allow lb	Body kN	Joint kN	Lesser kN	P_allow kN
7	29	N-80	LTC	676,000	597,000	597,000	477,600	3,007	2,655.6	2,655.6	2,124.5
7	29	N-80	BTC	676,000	746,000	676,000	540,800	3,007	3,318.4	3,007	2,405.6
7	29	C-90	LTC	760,000	648,000	648,000	518,400	3,380.6	2,882.4	2,882.4	2,306
7	29	C-90	BTC	760,000	768,000	760,000	608,000	3,380.6	3,416.2	3,380.6	2,704.5
7	29	C-95	LTC	803,000	683,000	683,000	546,400	3,571.9	3,038.1	3,038.1	2,430.5
7	29	C-95	BTC	803,000	808,000	803,000	642,400	3,571.9	3,594.2	3,571.9	2,857.5
7	29	T-95	LTC	803,000	683,000	683,000	546,400	3,571.9	3,038.1	3,038.1	2,430.5
7	29	T-95	BTC	803,000	808,000	803,000	642,400	3,571.9	3,594.2	3,571.9	2,857.5
7	29	P-110	LTC	929,000	797,000	797,000	637,600	4,132.4	3,545.2	3,545.2	2,836.2
7	29	P-110	BTC	929,000	955,000	929,000	743,200	4,132.4	4,248.1	4,132.4	3,305.9
7	29	Q-125	LTC	1,056,000	885,000	885,000	708,000	4,697.3	3,936.7	3,936.7	3,149.3
7	29	Q-125	BTC	1,056,000	1,045,000	1,045,000	836,000	4,697.3	4,648.4	4,648.4	3,718.7
7	32	L-80	LTC	745,000	661,000	661,000	528,800	3,313.9	2,940.3	2,940.3	2,352.2
7	32	L-80	BTC	745,000	791,000	745,000	596,000	3,313.9	3,518.5	3,313.9	2,651.1
7	32	N-80	LTC	745,000	672,000	672,000	537,600	3,313.9	2,989.2	2,989.2	2,391.4
7	32	N-80	BTC	745,000	823,000	745,000	596,000	3,313.9	3,660.9	3,313.9	2,651.1
7	32	C-90	LTC	839,000	729,000	729,000	583,200	3,732.1	3,242.8	3,242.8	2,594.2
7	32	C-90	BTC	839,000	847,000	839,000	671,200	3,732.1	3,767.6	3,732.1	2,985.6
7	32	C-95	LTC	885,000	768,000	768,000	614,400	3,936.7	3,416.2	3,416.2	2,733
7	32	C-95	BTC	885,000	891,000	885,000	708,000	3,936.7	3,963.4	3,936.7	3,149.3
7	32	T-95	LTC	885,000	768,000	768,000	614,400	3,936.7	3,416.2	3,416.2	2,733
7	32	T-95	BTC	885,000	891,000	885,000	708,000	3,936.7	3,963.4	3,936.7	3,149.3
7	32	P-110	LTC	1,025,000	897,000	897,000	717,600	4,559.4	3,990.1	3,990.1	3,192
7	32	P-110	BTC	1,025,000	1,053,000	1,025,000	820,000	4,559.4	4,684	4,559.4	3,647.5
7	32	Q-125	LTC	1,165,000	996,000	996,000	796,800	5,182.2	4,430.4	4,430.4	3,544.3

Check every figure against your own pipe records before you pull.

Casingjacks

Casingjacks LLC | sales@casingjack.com

Max pull tables

Data version 1.326cfcf0 | Build date 2026-11-17

Max pull

OD in	Weight lb/ft	Grade	Connection	Body lb	Joint lb	Lesser lb	P_allow lb	Body kN	Joint kN	Lesser kN	P_allow kN
7	32	Q-125	BTC	1,165,000	1,152,000	1,152,000	921,600	5,182.2	5,124.4	5,124.4	4,099.5
7	35	L-80	LTC	814,000	734,000	734,000	587,200	3,620.9	3,265	3,265	2,612
7	35	L-80	BTC	814,000	833,000	814,000	651,200	3,620.9	3,705.4	3,620.9	2,896.7
7	35	N-80	LTC	814,000	746,000	746,000	596,800	3,620.9	3,318.4	3,318.4	2,654.7
7	35	N-80	BTC	814,000	876,000	814,000	651,200	3,620.9	3,896.6	3,620.9	2,896.7
7	35	C-90	LTC	915,000	809,000	809,000	647,200	4,070.1	3,598.6	3,598.6	2,878.9
7	35	C-90	BTC	915,000	876,000	876,000	700,800	4,070.1	3,896.6	3,896.6	3,117.3
7	35	C-95	LTC	966,000	853,000	853,000	682,400	4,297	3,794.3	3,794.3	3,035.5
7	35	C-95	BTC	966,000	920,000	920,000	736,000	4,297	4,092.4	4,092.4	3,273.9
7	35	T-95	LTC	966,000	853,000	853,000	682,400	4,297	3,794.3	3,794.3	3,035.5
7	35	T-95	BTC	966,000	920,000	920,000	736,000	4,297	4,092.4	4,092.4	3,273.9
7	35	P-110	LTC	1,119,000	996,000	996,000	796,800	4,977.6	4,430.4	4,430.4	3,544.3
7	35	P-110	BTC	1,119,000	1,096,000	1,096,000	876,800	4,977.6	4,875.3	4,875.3	3,900.2
7	35	Q-125	LTC	1,272,000	1,106,000	1,106,000	884,800	5,658.1	4,919.7	4,919.7	3,935.8
7	35	Q-125	BTC	1,272,000	1,183,000	1,183,000	946,400	5,658.1	5,262.2	5,262.2	4,209.8
7	38	L-80	LTC	877,000	801,000	801,000	640,800	3,901.1	3,563	3,563	2,850.4
7	38	L-80	BTC	877,000	832,000	832,000	665,600	3,901.1	3,700.9	3,700.9	2,960.7
7	38	N-80	LTC	877,000	814,000	814,000	651,200	3,901.1	3,620.9	3,620.9	2,896.7
7	38	N-80	BTC	877,000	876,000	876,000	700,800	3,901.1	3,896.6	3,896.6	3,117.3
7	38	C-90	LTC	986,000	883,000	883,000	706,400	4,385.9	3,927.8	3,927.8	3,142.2
7	38	C-90	BTC	986,000	876,000	876,000	700,800	4,385.9	3,896.6	3,896.6	3,117.3
7	38	C-95	LTC	1,041,000	931,000	931,000	744,800	4,630.6	4,141.3	4,141.3	3,313
7	38	C-95	BTC	1,041,000	920,000	920,000	736,000	4,630.6	4,092.4	4,092.4	3,273.9
7	38	T-95	LTC	1,041,000	931,000	931,000	744,800	4,630.6	4,141.3	4,141.3	3,313
7	38	T-95	BTC	1,041,000	920,000	920,000	736,000	4,630.6	4,092.4	4,092.4	3,273.9

Check every figure against your own pipe records before you pull.

Casingjacks

Casingjacks LLC | sales@casingjack.com

Max pull tables

Data version 1.326cfcf0 | Build date 2026-11-17

Max pull

OD in	Weight lb/ft	Grade	Connection	Body lb	Joint lb	Lesser lb	P_allow lb	Body kN	Joint kN	Lesser kN	P_allow kN
7	38	P-110	LTC	1,205,000	1,087,000	1,087,000	869,600	5,360.1	4,835.2	4,835.2	3,868.2
7	38	P-110	BTC	1,205,000	1,096,000	1,096,000	876,800	5,360.1	4,875.3	4,875.3	3,900.2
7	38	Q-125	LTC	1,370,000	1,207,000	1,207,000	965,600	6,094.1	5,369	5,369	4,295.2
7	38	Q-125	BTC	1,370,000	1,183,000	1,183,000	946,400	6,094.1	5,262.2	5,262.2	4,209.8
7	41	C-90	LTC	1,069,000	903,000	903,000	722,400	4,755.1	4,016.7	4,016.7	3,213.4
7	41	C-90	BTC	1,069,000	876,000	876,000	700,800	4,755.1	3,896.6	3,896.6	3,117.3
7	41	T-95	LTC	1,129,000	952,000	952,000	761,600	5,022	4,234.7	4,234.7	3,387.8
7	41	T-95	BTC	1,129,000	920,000	920,000	736,000	5,022	4,092.4	4,092.4	3,273.9
7	41	P-110	LTC	1,307,000	1,111,000	1,111,000	888,800	5,813.8	4,942	4,942	3,953.6
7	41	P-110	BTC	1,307,000	1,096,000	1,096,000	876,800	5,813.8	4,875.3	4,875.3	3,900.2
7	41	Q-125	LTC	1,485,000	1,244,000	1,244,000	995,200	6,605.6	5,533.6	5,533.6	4,426.9
7	41	Q-125	BTC	1,485,000	1,183,000	1,183,000	946,400	6,605.6	5,262.2	5,262.2	4,209.8
7	42.7	C-90	Body only	1,127,000	Not recorded	1,127,000	901,600	5,013.1	Not recorded	5,013.1	4,010.5
7	42.7	T-95	Body only	1,189,000	Not recorded	1,189,000	951,200	5,288.9	Not recorded	5,288.9	4,231.1
7	46.4	C-90	Body only	1,226,000	Not recorded	1,226,000	980,800	5,453.5	Not recorded	5,453.5	4,362.8
7	46.4	T-95	Body only	1,294,000	Not recorded	1,294,000	1,035,200	5,756	Not recorded	5,756	4,604.8
7	50.1	C-90	Body only	1,325,000	Not recorded	1,325,000	1,060,000	5,893.9	Not recorded	5,893.9	4,715.1
7	50.1	T-95	Body only	1,399,000	Not recorded	1,399,000	1,119,200	6,223.1	Not recorded	6,223.1	4,978.4
7	53.6	C-90	Body only	1,421,000	Not recorded	1,421,000	1,136,800	6,320.9	Not recorded	6,320.9	5,056.7
7	53.6	T-95	Body only	1,500,000	Not recorded	1,500,000	1,200,000	6,672.3	Not recorded	6,672.3	5,337.9
7	57.1	C-90	Body only	1,515,000	Not recorded	1,515,000	1,212,000	6,739.1	Not recorded	6,739.1	5,391.2
7	57.1	T-95	Body only	1,600,000	Not recorded	1,600,000	1,280,000	7,117.2	Not recorded	7,117.2	5,693.7
7.625	24	H-40	STC	276,000	212,000	212,000	169,600	1,227.7	943	943	754.4
7.625	26.4	J-55	STC	414,000	315,000	315,000	252,000	1,841.6	1,401.2	1,401.2	1,121
7.625	26.4	J-55	LTC	414,000	346,000	346,000	276,800	1,841.6	1,539.1	1,539.1	1,231.3

Check every figure against your own pipe records before you pull.

Casingjacks

Casingjacks LLC | sales@casingjack.com

Max pull tables

Data version 1.326cfcf0 | Build date 2026-11-17

Max pull

OD in	Weight lb/ft	Grade	Connection	Body lb	Joint lb	Lesser lb	P_allow lb	Body kN	Joint kN	Lesser kN	P_allow kN
7.625	26.4	J-55	BTC	414,000	483,000	414,000	331,200	1,841.6	2,148.5	1,841.6	1,473.3
7.625	26.4	K-55	STC	414,000	342,000	342,000	273,600	1,841.6	1,521.3	1,521.3	1,217
7.625	26.4	K-55	LTC	414,000	377,000	377,000	301,600	1,841.6	1,677	1,677	1,341.6
7.625	26.4	K-55	BTC	414,000	581,000	414,000	331,200	1,841.6	2,584.4	1,841.6	1,473.3
7.625	26.4	M-65	STC	489,000	368,000	368,000	294,400	2,175.2	1,636.9	1,636.9	1,309.6
7.625	26.4	M-65	LTC	489,000	403,000	403,000	322,400	2,175.2	1,792.6	1,792.6	1,434.1
7.625	26.4	M-65	BTC	489,000	554,000	489,000	391,200	2,175.2	2,464.3	2,175.2	1,740.1
7.625	26.4	L-80	LTC	602,000	482,000	482,000	385,600	2,677.8	2,144	2,144	1,715.2
7.625	26.4	L-80	BTC	602,000	635,000	602,000	481,600	2,677.8	2,824.6	2,677.8	2,142.3
7.625	26.4	N-80	LTC	602,000	490,000	490,000	392,000	2,677.8	2,179.6	2,179.6	1,743.7
7.625	26.4	N-80	BTC	602,000	659,000	602,000	481,600	2,677.8	2,931.4	2,677.8	2,142.3
7.625	26.4	C-90	LTC	677,000	532,000	532,000	425,600	3,011.4	2,366.5	2,366.5	1,893.2
7.625	26.4	C-90	BTC	677,000	681,000	677,000	541,600	3,011.4	3,029.2	3,011.4	2,409.2
7.625	26.4	C-95	LTC	714,000	560,000	560,000	448,000	3,176	2,491	2,491	1,992.8
7.625	26.4	C-95	BTC	714,000	716,000	714,000	571,200	3,176	3,184.9	3,176	2,540.8
7.625	26.4	T-95	LTC	714,000	560,000	560,000	448,000	3,176	2,491	2,491	1,992.8
7.625	26.4	T-95	BTC	714,000	716,000	714,000	571,200	3,176	3,184.9	3,176	2,540.8
7.625	26.4	P-110	LTC	827,000	654,000	654,000	523,200	3,678.7	2,909.1	2,909.1	2,327.3
7.625	26.4	P-110	BTC	827,000	845,000	827,000	661,600	3,678.7	3,758.7	3,678.7	2,942.9
7.625	29.7	M-65	LTC	555,000	474,000	474,000	379,200	2,468.8	2,108.5	2,108.5	1,686.8
7.625	29.7	M-65	BTC	555,000	629,000	555,000	444,000	2,468.8	2,797.9	2,468.8	1,975
7.625	29.7	L-80	LTC	683,000	566,000	566,000	452,800	3,038.1	2,517.7	2,517.7	2,014.2
7.625	29.7	L-80	BTC	683,000	721,000	683,000	546,400	3,038.1	3,207.2	3,038.1	2,430.5
7.625	29.7	N-80	LTC	683,000	575,000	575,000	460,000	3,038.1	2,557.7	2,557.7	2,046.2
7.625	29.7	N-80	BTC	683,000	749,000	683,000	546,400	3,038.1	3,331.7	3,038.1	2,430.5

Check every figure against your own pipe records before you pull.

Casingjacks

Casingjacks LLC | sales@casingjack.com

Max pull tables

Data version 1.326cfcf0 | Build date 2026-11-17

Max pull

OD in	Weight lb/ft	Grade	Connection	Body lb	Joint lb	Lesser lb	P_allow lb	Body kN	Joint kN	Lesser kN	P_allow kN
7.625	29.7	C-90	LTC	769,000	625,000	625,000	500,000	3,420.7	2,780.1	2,780.1	2,224.1
7.625	29.7	C-90	BTC	769,000	773,000	769,000	615,200	3,420.7	3,438.5	3,420.7	2,736.5
7.625	29.7	C-95	LTC	811,000	659,000	659,000	527,200	3,607.5	2,931.4	2,931.4	2,345.1
7.625	29.7	C-95	BTC	811,000	813,000	811,000	648,800	3,607.5	3,616.4	3,607.5	2,886
7.625	29.7	T-95	LTC	811,000	659,000	659,000	527,200	3,607.5	2,931.4	2,931.4	2,345.1
7.625	29.7	T-95	BTC	811,000	813,000	811,000	648,800	3,607.5	3,616.4	3,607.5	2,886
7.625	29.7	P-110	LTC	940,000	769,000	769,000	615,200	4,181.3	3,420.7	3,420.7	2,736.5
7.625	29.7	P-110	BTC	940,000	960,000	940,000	752,000	4,181.3	4,270.3	4,181.3	3,345.1
7.625	33.7	L-80	LTC	778,000	664,000	664,000	531,200	3,460.7	2,953.6	2,953.6	2,362.9
7.625	33.7	L-80	BTC	778,000	820,000	778,000	622,400	3,460.7	3,647.5	3,460.7	2,768.6
7.625	33.7	N-80	LTC	778,000	674,000	674,000	539,200	3,460.7	2,998.1	2,998.1	2,398.5
7.625	33.7	N-80	BTC	778,000	852,000	778,000	622,400	3,460.7	3,789.9	3,460.7	2,768.6
7.625	33.7	C-90	LTC	875,000	733,000	733,000	586,400	3,892.2	3,260.5	3,260.5	2,608.4
7.625	33.7	C-90	BTC	875,000	880,000	875,000	700,000	3,892.2	3,914.4	3,892.2	3,113.8
7.625	33.7	C-95	LTC	923,000	772,000	772,000	617,600	4,105.7	3,434	3,434	2,747.2
7.625	33.7	C-95	BTC	923,000	925,000	923,000	738,400	4,105.7	4,114.6	4,105.7	3,284.6
7.625	33.7	T-95	LTC	923,000	772,000	772,000	617,600	4,105.7	3,434	3,434	2,747.2
7.625	33.7	T-95	BTC	923,000	925,000	923,000	738,400	4,105.7	4,114.6	4,105.7	3,284.6
7.625	33.7	P-110	LTC	1,069,000	901,000	901,000	720,800	4,755.1	4,007.8	4,007.8	3,206.3
7.625	33.7	P-110	BTC	1,069,000	1,093,000	1,069,000	855,200	4,755.1	4,861.9	4,755.1	3,804.1
7.625	33.7	Q-125	LTC	1,215,000	1,009,000	1,009,000	807,200	5,404.6	4,488.3	4,488.3	3,590.6
7.625	33.7	Q-125	BTC	1,215,000	1,197,000	1,197,000	957,600	5,404.6	5,324.5	5,324.5	4,259.6
7.625	39	L-80	LTC	895,000	786,000	786,000	628,800	3,981.2	3,496.3	3,496.3	2,797
7.625	39	L-80	BTC	895,000	945,000	895,000	716,000	3,981.2	4,203.6	3,981.2	3,184.9
7.625	39	N-80	LTC	895,000	798,000	798,000	638,400	3,981.2	3,549.7	3,549.7	2,839.7

Check every figure against your own pipe records before you pull.

Casingjacks

Casingjacks LLC | sales@casingjack.com

Max pull tables

Data version 1.326cfcf0 | Build date 2026-11-17

Max pull

OD in	Weight lb/ft	Grade	Connection	Body lb	Joint lb	Lesser lb	P_allow lb	Body kN	Joint kN	Lesser kN	P_allow kN
7.625	39	N-80	BTC	895,000	981,000	895,000	716,000	3,981.2	4,363.7	3,981.2	3,184.9
7.625	39	C-90	LTC	1,007,000	867,000	867,000	693,600	4,479.4	3,856.6	3,856.6	3,085.3
7.625	39	C-90	BTC	1,007,000	1,013,000	1,007,000	805,600	4,479.4	4,506	4,479.4	3,583.5
7.625	39	C-95	LTC	1,063,000	914,000	914,000	731,200	4,728.5	4,065.7	4,065.7	3,252.5
7.625	39	C-95	BTC	1,063,000	1,065,000	1,063,000	850,400	4,728.5	4,737.4	4,728.5	3,782.8
7.625	39	T-95	LTC	1,063,000	914,000	914,000	731,200	4,728.5	4,065.7	4,065.7	3,252.5
7.625	39	T-95	BTC	1,063,000	1,065,000	1,063,000	850,400	4,728.5	4,737.4	4,728.5	3,782.8
7.625	39	P-110	LTC	1,231,000	1,066,000	1,066,000	852,800	5,475.8	4,741.8	4,741.8	3,793.4
7.625	39	P-110	BTC	1,231,000	1,258,000	1,231,000	984,800	5,475.8	5,595.9	5,475.8	4,380.6
7.625	39	Q-125	LTC	1,399,000	1,194,000	1,194,000	955,200	6,223.1	5,311.2	5,311.2	4,248.9
7.625	39	Q-125	BTC	1,399,000	1,379,000	1,379,000	1,103,200	6,223.1	6,134.1	6,134.1	4,907.3
7.625	42.8	L-80	LTC	998,000	891,000	891,000	712,800	4,439.3	3,963.4	3,963.4	3,170.7
7.625	42.8	L-80	BTC	998,000	1,053,000	998,000	798,400	4,439.3	4,684	4,439.3	3,551.5
7.625	42.8	N-80	LTC	998,000	905,000	905,000	724,000	4,439.3	4,025.6	4,025.6	3,220.5
7.625	42.8	N-80	BTC	998,000	1,093,000	998,000	798,400	4,439.3	4,861.9	4,439.3	3,551.5
7.625	42.8	C-90	LTC	1,122,000	983,000	983,000	786,400	4,990.9	4,372.6	4,372.6	3,498.1
7.625	42.8	C-90	BTC	1,122,000	1,129,000	1,122,000	897,600	4,990.9	5,022	4,990.9	3,992.7
7.625	42.8	C-95	LTC	1,185,000	1,037,000	1,037,000	829,600	5,271.1	4,612.8	4,612.8	3,690.2
7.625	42.8	C-95	BTC	1,185,000	1,187,000	1,185,000	948,000	5,271.1	5,280	5,271.1	4,216.9
7.625	42.8	T-95	LTC	1,185,000	1,037,000	1,037,000	829,600	5,271.1	4,612.8	4,612.8	3,690.2
7.625	42.8	T-95	BTC	1,185,000	1,187,000	1,185,000	948,000	5,271.1	5,280	5,271.1	4,216.9
7.625	42.8	P-110	LTC	1,372,000	1,210,000	1,210,000	968,000	6,103	5,382.3	5,382.3	4,305.9
7.625	42.8	P-110	BTC	1,372,000	1,402,000	1,372,000	1,097,600	6,103	6,236.4	6,103	4,882.4
7.625	42.8	Q-125	LTC	1,559,000	1,355,000	1,355,000	1,084,000	6,934.8	6,027.3	6,027.3	4,821.9
7.625	42.8	Q-125	BTC	1,559,000	1,536,000	1,536,000	1,228,800	6,934.8	6,832.5	6,832.5	5,466

Check every figure against your own pipe records before you pull.

Casingjacks

Casingjacks LLC | sales@casingjack.com

Max pull tables

Data version 1.326cfcf0 | Build date 2026-11-17

Max pull

OD in	Weight lb/ft	Grade	Connection	Body lb	Joint lb	Lesser lb	P_allow lb	Body kN	Joint kN	Lesser kN	P_allow kN
7.625	45.3	L-80	LTC	1,051,000	947,000	947,000	757,600	4,675.1	4,212.5	4,212.5	3,370
7.625	45.3	L-80	BTC	1,051,000	1,109,000	1,051,000	840,800	4,675.1	4,933.1	4,675.1	3,740.1
7.625	45.3	N-80	LTC	1,051,000	962,000	962,000	769,600	4,675.1	4,279.2	4,279.2	3,423.4
7.625	45.3	N-80	BTC	1,051,000	1,152,000	1,051,000	840,800	4,675.1	5,124.4	4,675.1	3,740.1
7.625	45.3	C-90	LTC	1,183,000	1,045,000	1,045,000	836,000	5,262.2	4,648.4	4,648.4	3,718.7
7.625	45.3	C-90	BTC	1,183,000	1,189,000	1,183,000	946,400	5,262.2	5,288.9	5,262.2	4,209.8
7.625	45.3	C-95	LTC	1,248,000	1,101,000	1,101,000	880,800	5,551.4	4,897.5	4,897.5	3,918
7.625	45.3	C-95	BTC	1,248,000	1,251,000	1,248,000	998,400	5,551.4	5,564.7	5,551.4	4,441.1
7.625	45.3	P-110	LTC	1,446,000	1,285,000	1,285,000	1,028,000	6,432.1	5,716	5,716	4,572.8
7.625	45.3	P-110	BTC	1,446,000	1,477,000	1,446,000	1,156,800	6,432.1	6,570	6,432.1	5,145.7
7.625	45.3	Q-125	LTC	1,643,000	1,439,000	1,439,000	1,151,200	7,308.4	6,401	6,401	5,120.8
7.625	45.3	Q-125	BTC	1,643,000	1,619,000	1,619,000	1,295,200	7,308.4	7,201.7	7,201.7	5,761.3
7.625	47.1	L-80	LTC	1,100,000	997,000	997,000	797,600	4,893	4,434.9	4,434.9	3,547.9
7.625	47.1	L-80	BTC	1,100,000	1,160,000	1,100,000	880,000	4,893	5,159.9	4,893	3,914.4
7.625	47.1	N-80	LTC	1,100,000	1,013,000	1,013,000	810,400	4,893	4,506	4,506	3,604.8
7.625	47.1	N-80	BTC	1,100,000	1,205,000	1,100,000	880,000	4,893	5,360.1	4,893	3,914.4
7.625	47.1	C-90	LTC	1,237,000	1,100,000	1,100,000	880,000	5,502.5	4,893	4,893	3,914.4
7.625	47.1	C-90	BTC	1,237,000	1,238,000	1,237,000	989,600	5,502.5	5,506.9	5,502.5	4,402
7.625	47.1	C-95	LTC	1,306,000	1,159,000	1,159,000	927,200	5,809.4	5,155.5	5,155.5	4,124.4
7.625	47.1	C-95	BTC	1,306,000	1,300,000	1,300,000	1,040,000	5,809.4	5,782.7	5,782.7	4,626.2
7.625	47.1	T-95	LTC	1,306,000	1,159,000	1,159,000	927,200	5,809.4	5,155.5	5,155.5	4,124.4
7.625	47.1	T-95	BTC	1,306,000	1,300,000	1,300,000	1,040,000	5,809.4	5,782.7	5,782.7	4,626.2
7.625	47.1	P-110	LTC	1,512,000	1,353,000	1,353,000	1,082,400	6,725.7	6,018.4	6,018.4	4,814.8
7.625	47.1	P-110	BTC	1,512,000	1,545,000	1,512,000	1,209,600	6,725.7	6,872.5	6,725.7	5,380.6
7.625	47.1	Q-125	LTC	1,718,000	1,515,000	1,515,000	1,212,000	7,642	6,739.1	6,739.1	5,391.2

Check every figure against your own pipe records before you pull.

Casingjacks

Casingjacks LLC | sales@casingjack.com

Max pull tables

Data version 1.326cfcf0 | Build date 2026-11-17

Max pull

OD in	Weight lb/ft	Grade	Connection	Body lb	Joint lb	Lesser lb	P_allow lb	Body kN	Joint kN	Lesser kN	P_allow kN
7.625	47.1	Q-125	BTC	1,718,000	1,672,000	1,672,000	1,337,600	7,642	7,437.4	7,437.4	5,949.9
7.625	51.2	C-90	Body only	1,348,000	Not recorded	1,348,000	1,078,400	5,996.2	Not recorded	5,996.2	4,797
7.625	51.2	T-95	Body only	1,423,000	Not recorded	1,423,000	1,138,400	6,329.8	Not recorded	6,329.8	5,063.9
7.625	55.3	C-90	Body only	1,458,000	Not recorded	1,458,000	1,166,400	6,485.5	Not recorded	6,485.5	5,188.4
7.625	55.3	T-95	Body only	1,539,000	Not recorded	1,539,000	1,231,200	6,845.8	Not recorded	6,845.8	5,476.7
7.75	46.1	L-80	LTC	1,070,000	841,000	841,000	672,800	4,759.6	3,741	3,741	2,992.8
7.75	46.1	L-80	BTC	1,070,000	1,001,000	1,001,000	800,800	4,759.6	4,452.7	4,452.7	3,562.1
7.75	46.1	C-90	LTC	1,204,000	928,000	928,000	742,400	5,355.7	4,127.9	4,127.9	3,302.4
7.75	46.1	C-90	BTC	1,204,000	1,074,000	1,074,000	859,200	5,355.7	4,777.4	4,777.4	3,821.9
7.75	46.1	C-95	LTC	1,271,000	978,000	978,000	782,400	5,653.7	4,350.4	4,350.4	3,480.3
7.75	46.1	C-95	BTC	1,271,000	1,129,000	1,129,000	903,200	5,653.7	5,022	5,022	4,017.6
7.75	46.1	T-95	LTC	1,271,000	978,000	978,000	782,400	5,653.7	4,350.4	4,350.4	3,480.3
7.75	46.1	T-95	BTC	1,271,000	1,129,000	1,129,000	903,200	5,653.7	5,022	5,022	4,017.6
7.75	46.1	P-110	LTC	1,471,000	1,142,000	1,142,000	913,600	6,543.3	5,079.9	5,079.9	4,063.9
7.75	46.1	P-110	BTC	1,471,000	1,334,000	1,334,000	1,067,200	6,543.3	5,933.9	5,933.9	4,747.1
7.75	46.1	Q-125	LTC	1,672,000	1,279,000	1,279,000	1,023,200	7,437.4	5,689.3	5,689.3	4,551.4
7.75	46.1	Q-125	BTC	1,672,000	1,462,000	1,462,000	1,169,600	7,437.4	6,503.3	6,503.3	5,202.6
8.625	24	J-55	STC	381,000	244,000	244,000	195,200	1,694.8	1,085.4	1,085.4	868.3
8.625	24	K-55	STC	381,000	263,000	263,000	210,400	1,694.8	1,169.9	1,169.9	935.9
8.625	24	M-65	STC	451,000	302,000	302,000	241,600	2,006.1	1,343.4	1,343.4	1,074.7
8.625	28	H-40	STC	318,000	233,000	233,000	186,400	1,414.5	1,036.4	1,036.4	829.1
8.625	32	H-40	STC	366,000	279,000	279,000	223,200	1,628	1,241.1	1,241.1	992.8
8.625	32	J-55	STC	503,000	372,000	372,000	297,600	2,237.5	1,654.7	1,654.7	1,323.8
8.625	32	J-55	LTC	503,000	417,000	417,000	333,600	2,237.5	1,854.9	1,854.9	1,483.9
8.625	32	J-55	BTC	503,000	579,000	503,000	402,400	2,237.5	2,575.5	2,237.5	1,790

Check every figure against your own pipe records before you pull.

Casingjacks

Casingjacks LLC | sales@casingjack.com

Max pull tables

Data version 1.326cfcf0 | Build date 2026-11-17

Max pull

OD in	Weight lb/ft	Grade	Connection	Body lb	Joint lb	Lesser lb	P_allow lb	Body kN	Joint kN	Lesser kN	P_allow kN
8.625	32	K-55	STC	503,000	402,000	402,000	321,600	2,237.5	1,788.2	1,788.2	1,430.5
8.625	32	K-55	LTC	503,000	452,000	452,000	361,600	2,237.5	2,010.6	2,010.6	1,608.5
8.625	32	K-55	BTC	503,000	690,000	503,000	402,400	2,237.5	3,069.3	2,237.5	1,790
8.625	32	M-65	STC	595,000	435,000	435,000	348,000	2,646.7	1,935	1,935	1,548
8.625	32	M-65	LTC	595,000	487,000	487,000	389,600	2,646.7	2,166.3	2,166.3	1,733
8.625	32	M-65	BTC	595,000	664,000	595,000	476,000	2,646.7	2,953.6	2,646.7	2,117.4
8.625	36	J-55	STC	568,000	434,000	434,000	347,200	2,526.6	1,930.5	1,930.5	1,544.4
8.625	36	J-55	LTC	568,000	486,000	486,000	388,800	2,526.6	2,161.8	2,161.8	1,729.5
8.625	36	J-55	BTC	568,000	654,000	568,000	454,400	2,526.6	2,909.1	2,526.6	2,021.3
8.625	36	K-55	STC	568,000	468,000	468,000	374,400	2,526.6	2,081.8	2,081.8	1,665.4
8.625	36	K-55	LTC	568,000	526,000	526,000	420,800	2,526.6	2,339.8	2,339.8	1,871.8
8.625	36	K-55	BTC	568,000	780,000	568,000	454,400	2,526.6	3,469.6	2,526.6	2,021.3
8.625	36	M-65	STC	672,000	506,000	506,000	404,800	2,989.2	2,250.8	2,250.8	1,800.6
8.625	36	M-65	LTC	672,000	567,000	567,000	453,600	2,989.2	2,522.1	2,522.1	2,017.7
8.625	36	M-65	BTC	672,000	751,000	672,000	537,600	2,989.2	3,340.6	2,989.2	2,391.4
8.625	36	L-80	LTC	827,000	678,000	678,000	542,400	3,678.7	3,015.9	3,015.9	2,412.7
8.625	36	L-80	BTC	827,000	864,000	827,000	661,600	3,678.7	3,843.3	3,678.7	2,942.9
8.625	36	N-80	LTC	827,000	688,000	688,000	550,400	3,678.7	3,060.4	3,060.4	2,448.3
8.625	36	N-80	BTC	827,000	895,000	827,000	661,600	3,678.7	3,981.2	3,678.7	2,942.9
8.625	40	M-65	LTC	751,000	649,000	649,000	519,200	3,340.6	2,886.9	2,886.9	2,309.5
8.625	40	M-65	BTC	751,000	839,000	751,000	600,800	3,340.6	3,732.1	3,340.6	2,672.5
8.625	40	L-80	LTC	925,000	776,000	776,000	620,800	4,114.6	3,451.8	3,451.8	2,761.5
8.625	40	L-80	BTC	925,000	966,000	925,000	740,000	4,114.6	4,297	4,114.6	3,291.7
8.625	40	N-80	LTC	925,000	788,000	788,000	630,400	4,114.6	3,505.2	3,505.2	2,804.2
8.625	40	N-80	BTC	925,000	1,001,000	925,000	740,000	4,114.6	4,452.7	4,114.6	3,291.7

Check every figure against your own pipe records before you pull.

Casingjacks

Casingjacks LLC | sales@casingjack.com

Max pull tables

Data version 1.326cfcf0 | Build date 2026-11-17

Max pull

OD in	Weight lb/ft	Grade	Connection	Body lb	Joint lb	Lesser lb	P_allow lb	Body kN	Joint kN	Lesser kN	P_allow kN
8.625	40	C-90	LTC	1,040,000	858,000	858,000	686,400	4,626.2	3,816.6	3,816.6	3,053.3
8.625	40	C-90	BTC	1,040,000	1,038,000	1,038,000	830,400	4,626.2	4,617.3	4,617.3	3,693.8
8.625	40	C-95	LTC	1,098,000	904,000	904,000	723,200	4,884.1	4,021.2	4,021.2	3,217
8.625	40	C-95	BTC	1,098,000	1,092,000	1,092,000	873,600	4,884.1	4,857.5	4,857.5	3,886
8.625	40	T-95	LTC	1,098,000	904,000	904,000	723,200	4,884.1	4,021.2	4,021.2	3,217
8.625	40	T-95	BTC	1,098,000	1,092,000	1,092,000	873,600	4,884.1	4,857.5	4,857.5	3,886
8.625	40	P-110	LTC	1,271,000	1,055,000	1,055,000	844,000	5,653.7	4,692.9	4,692.9	3,754.3
8.625	40	P-110	BTC	1,271,000	1,228,000	1,228,000	982,400	5,653.7	5,462.4	5,462.4	4,369.9
8.625	44	L-80	LTC	1,021,000	874,000	874,000	699,200	4,541.6	3,887.7	3,887.7	3,110.2
8.625	44	L-80	BTC	1,021,000	1,066,000	1,021,000	816,800	4,541.6	4,741.8	4,541.6	3,633.3
8.625	44	N-80	LTC	1,021,000	887,000	887,000	709,600	4,541.6	3,945.6	3,945.6	3,156.5
8.625	44	N-80	BTC	1,021,000	1,105,000	1,021,000	816,800	4,541.6	4,915.3	4,541.6	3,633.3
8.625	44	C-90	LTC	1,149,000	965,000	965,000	772,000	5,111	4,292.5	4,292.5	3,434
8.625	44	C-90	BTC	1,149,000	1,146,000	1,146,000	916,800	5,111	5,097.7	5,097.7	4,078.1
8.625	44	C-95	LTC	1,212,000	1,017,000	1,017,000	813,600	5,391.2	4,523.8	4,523.8	3,619.1
8.625	44	C-95	BTC	1,212,000	1,206,000	1,206,000	964,800	5,391.2	5,364.6	5,364.6	4,291.6
8.625	44	T-95	LTC	1,212,000	1,017,000	1,017,000	813,600	5,391.2	4,523.8	4,523.8	3,619.1
8.625	44	T-95	BTC	1,212,000	1,206,000	1,206,000	964,800	5,391.2	5,364.6	5,364.6	4,291.6
8.625	44	P-110	LTC	1,404,000	1,186,000	1,186,000	948,800	6,245.3	5,275.6	5,275.6	4,220.5
8.625	44	P-110	BTC	1,404,000	1,423,000	1,404,000	1,123,200	6,245.3	6,329.8	6,245.3	4,996.2
8.625	44	Q-125	LTC	1,595,000	1,330,000	1,330,000	1,064,000	7,094.9	5,916.1	5,916.1	4,732.9
8.625	44	Q-125	BTC	1,595,000	1,562,000	1,562,000	1,249,600	7,094.9	6,948.1	6,948.1	5,558.5
8.625	49	L-80	LTC	1,129,000	983,000	983,000	786,400	5,022	4,372.6	4,372.6	3,498.1
8.625	49	L-80	BTC	1,129,000	1,180,000	1,129,000	903,200	5,022	5,248.9	5,022	4,017.6
8.625	49	N-80	LTC	1,129,000	997,000	997,000	797,600	5,022	4,434.9	4,434.9	3,547.9

Check every figure against your own pipe records before you pull.

Casingjacks

Casingjacks LLC | sales@casingjack.com

Max pull tables

Data version 1.326cfcf0 | Build date 2026-11-17

Max pull

OD in	Weight lb/ft	Grade	Connection	Body lb	Joint lb	Lesser lb	P_allow lb	Body kN	Joint kN	Lesser kN	P_allow kN
8.625	49	N-80	BTC	1,129,000	1,222,000	1,129,000	903,200	5,022	5,435.7	5,022	4,017.6
8.625	49	C-95	LTC	1,341,000	1,144,000	1,144,000	915,200	5,965.1	5,088.8	5,088.8	4,071
8.625	49	C-95	BTC	1,341,000	1,334,000	1,334,000	1,067,200	5,965.1	5,933.9	5,933.9	4,747.1
8.625	49	T-95	LTC	1,341,000	1,144,000	1,144,000	915,200	5,965.1	5,088.8	5,088.8	4,071
8.625	49	T-95	BTC	1,341,000	1,334,000	1,334,000	1,067,200	5,965.1	5,933.9	5,933.9	4,747.1
8.625	49	P-110	LTC	1,553,000	1,335,000	1,335,000	1,068,000	6,908.1	5,938.4	5,938.4	4,750.7
8.625	49	P-110	BTC	1,553,000	1,574,000	1,553,000	1,242,400	6,908.1	7,001.5	6,908.1	5,526.5
8.625	49	Q-125	LTC	1,765,000	1,496,000	1,496,000	1,196,800	7,851.1	6,654.5	6,654.5	5,323.6
8.625	49	Q-125	BTC	1,765,000	1,728,000	1,728,000	1,382,400	7,851.1	7,686.5	7,686.5	6,149.2
9.625	32.3	H-40	STC	365,000	254,000	254,000	203,200	1,623.6	1,129.8	1,129.8	903.9
9.625	36	H-40	STC	410,000	294,000	294,000	235,200	1,823.8	1,307.8	1,307.8	1,046.2
9.625	36	J-55	STC	564,000	394,000	394,000	315,200	2,508.8	1,752.6	1,752.6	1,402.1
9.625	36	J-55	LTC	564,000	453,000	453,000	362,400	2,508.8	2,015	2,015	1,612
9.625	36	J-55	BTC	564,000	639,000	564,000	451,200	2,508.8	2,842.4	2,508.8	2,007
9.625	36	K-55	STC	564,000	423,000	423,000	338,400	2,508.8	1,881.6	1,881.6	1,505.3
9.625	36	K-55	LTC	564,000	489,000	489,000	391,200	2,508.8	2,175.2	2,175.2	1,740.1
9.625	36	K-55	BTC	564,000	755,000	564,000	451,200	2,508.8	3,358.4	2,508.8	2,007
9.625	36	M-65	STC	667,000	460,000	460,000	368,000	2,967	2,046.2	2,046.2	1,636.9
9.625	36	M-65	LTC	667,000	529,000	529,000	423,200	2,967	2,353.1	2,353.1	1,882.5
9.625	36	M-65	BTC	667,000	734,000	667,000	533,600	2,967	3,265	2,967	2,373.6
9.625	40	J-55	STC	630,000	452,000	452,000	361,600	2,802.4	2,010.6	2,010.6	1,608.5
9.625	40	J-55	LTC	630,000	520,000	520,000	416,000	2,802.4	2,313.1	2,313.1	1,850.5
9.625	40	J-55	BTC	630,000	714,000	630,000	504,000	2,802.4	3,176	2,802.4	2,241.9
9.625	40	K-55	STC	630,000	486,000	486,000	388,800	2,802.4	2,161.8	2,161.8	1,729.5
9.625	40	K-55	LTC	630,000	561,000	561,000	448,800	2,802.4	2,495.5	2,495.5	1,996.4

Check every figure against your own pipe records before you pull.

Casingjacks

Casingjacks LLC | sales@casingjack.com

Max pull tables

Data version 1.326cfcf0 | Build date 2026-11-17

Max pull

OD in	Weight lb/ft	Grade	Connection	Body lb	Joint lb	Lesser lb	P_allow lb	Body kN	Joint kN	Lesser kN	P_allow kN
9.625	40	K-55	BTC	630,000	843,000	630,000	504,000	2,802.4	3,749.9	2,802.4	2,241.9
9.625	40	M-65	STC	745,000	528,000	528,000	422,400	3,313.9	2,348.7	2,348.7	1,878.9
9.625	40	M-65	LTC	745,000	608,000	608,000	486,400	3,313.9	2,704.5	2,704.5	2,163.6
9.625	40	M-65	BTC	745,000	823,000	745,000	596,000	3,313.9	3,660.9	3,313.9	2,651.1
9.625	40	L-80	LTC	916,000	727,000	727,000	581,600	4,074.6	3,233.9	3,233.9	2,587.1
9.625	40	L-80	BTC	916,000	947,000	916,000	732,800	4,074.6	4,212.5	4,074.6	3,259.7
9.625	40	N-80	LTC	916,000	737,000	737,000	589,600	4,074.6	3,278.3	3,278.3	2,622.7
9.625	40	N-80	BTC	916,000	979,000	916,000	732,800	4,074.6	4,354.8	4,074.6	3,259.7
9.625	40	C-90	LTC	1,031,000	804,000	804,000	643,200	4,586.1	3,576.4	3,576.4	2,861.1
9.625	40	C-90	BTC	1,031,000	1,021,000	1,021,000	816,800	4,586.1	4,541.6	4,541.6	3,633.3
9.625	40	C-95	LTC	1,088,000	847,000	847,000	677,600	4,839.7	3,767.6	3,767.6	3,014.1
9.625	40	C-95	BTC	1,088,000	1,074,000	1,074,000	859,200	4,839.7	4,777.4	4,777.4	3,821.9
9.625	40	T-95	LTC	1,088,000	847,000	847,000	677,600	4,839.7	3,767.6	3,767.6	3,014.1
9.625	40	T-95	BTC	1,088,000	1,074,000	1,074,000	859,200	4,839.7	4,777.4	4,777.4	3,821.9
9.625	43.5	M-65	LTC	816,000	679,000	679,000	543,200	3,629.7	3,020.3	3,020.3	2,416.3
9.625	43.5	M-65	BTC	816,000	899,000	816,000	652,800	3,629.7	3,999	3,629.7	2,903.8
9.625	43.5	L-80	LTC	1,005,000	813,000	813,000	650,400	4,470.5	3,616.4	3,616.4	2,893.1
9.625	43.5	L-80	BTC	1,005,000	1,038,000	1,005,000	804,000	4,470.5	4,617.3	4,470.5	3,576.4
9.625	43.5	N-80	LTC	1,005,000	825,000	825,000	660,000	4,470.5	3,669.8	3,669.8	2,935.8
9.625	43.5	N-80	BTC	1,005,000	1,074,000	1,005,000	804,000	4,470.5	4,777.4	4,470.5	3,576.4
9.625	43.5	C-90	LTC	1,130,000	899,000	899,000	719,200	5,026.5	3,999	3,999	3,199.2
9.625	43.5	C-90	BTC	1,130,000	1,119,000	1,119,000	895,200	5,026.5	4,977.6	4,977.6	3,982
9.625	43.5	C-95	LTC	1,193,000	948,000	948,000	758,400	5,306.7	4,216.9	4,216.9	3,373.5
9.625	43.5	C-95	BTC	1,193,000	1,178,000	1,178,000	942,400	5,306.7	5,240	5,240	4,192
9.625	43.5	T-95	LTC	1,193,000	948,000	948,000	758,400	5,306.7	4,216.9	4,216.9	3,373.5

Check every figure against your own pipe records before you pull.

Casingjacks

Casingjacks LLC | sales@casingjack.com

Max pull tables

Data version 1.326cfcf0 | Build date 2026-11-17

Max pull

OD in	Weight lb/ft	Grade	Connection	Body lb	Joint lb	Lesser lb	P_allow lb	Body kN	Joint kN	Lesser kN	P_allow kN
9.625	43.5	T-95	BTC	1,193,000	1,178,000	1,178,000	942,400	5,306.7	5,240	5,240	4,192
9.625	43.5	P-110	LTC	1,381,000	1,106,000	1,106,000	884,800	6,143	4,919.7	4,919.7	3,935.8
9.625	43.5	P-110	BTC	1,381,000	1,388,000	1,381,000	1,104,800	6,143	6,174.1	6,143	4,914.4
9.625	43.5	Q-125	LTC	1,570,000	1,240,000	1,240,000	992,000	6,983.7	5,515.8	5,515.8	4,412.6
9.625	43.5	Q-125	BTC	1,570,000	1,527,000	1,527,000	1,221,600	6,983.7	6,792.4	6,792.4	5,433.9
9.625	47	L-80	LTC	1,086,000	893,000	893,000	714,400	4,830.8	3,972.3	3,972.3	3,177.8
9.625	47	L-80	BTC	1,086,000	1,122,000	1,086,000	868,800	4,830.8	4,990.9	4,830.8	3,864.6
9.625	47	N-80	LTC	1,086,000	905,000	905,000	724,000	4,830.8	4,025.6	4,025.6	3,220.5
9.625	47	N-80	BTC	1,086,000	1,161,000	1,086,000	868,800	4,830.8	5,164.4	4,830.8	3,864.6
9.625	47	C-90	LTC	1,221,000	987,000	987,000	789,600	5,431.3	4,390.4	4,390.4	3,512.3
9.625	47	C-90	BTC	1,221,000	1,210,000	1,210,000	968,000	5,431.3	5,382.3	5,382.3	4,305.9
9.625	47	C-95	LTC	1,289,000	1,040,000	1,040,000	832,000	5,733.8	4,626.2	4,626.2	3,700.9
9.625	47	C-95	BTC	1,289,000	1,273,000	1,273,000	1,018,400	5,733.8	5,662.6	5,662.6	4,530.1
9.625	47	T-95	LTC	1,289,000	1,040,000	1,040,000	832,000	5,733.8	4,626.2	4,626.2	3,700.9
9.625	47	T-95	BTC	1,289,000	1,273,000	1,273,000	1,018,400	5,733.8	5,662.6	5,662.6	4,530.1
9.625	47	P-110	LTC	1,493,000	1,213,000	1,213,000	970,400	6,641.2	5,395.7	5,395.7	4,316.6
9.625	47	P-110	BTC	1,493,000	1,500,000	1,493,000	1,194,400	6,641.2	6,672.3	6,641.2	5,313
9.625	47	Q-125	LTC	1,697,000	1,361,000	1,361,000	1,088,800	7,548.6	6,054	6,054	4,843.2
9.625	47	Q-125	BTC	1,697,000	1,650,000	1,650,000	1,320,000	7,548.6	7,339.6	7,339.6	5,871.7
9.625	53.5	L-80	LTC	1,244,000	1,047,000	1,047,000	837,600	5,533.6	4,657.3	4,657.3	3,725.8
9.625	53.5	L-80	BTC	1,244,000	1,286,000	1,244,000	995,200	5,533.6	5,720.4	5,533.6	4,426.9
9.625	53.5	N-80	LTC	1,244,000	1,062,000	1,062,000	849,600	5,533.6	4,724	4,724	3,779.2
9.625	53.5	N-80	BTC	1,244,000	1,329,000	1,244,000	995,200	5,533.6	5,911.7	5,533.6	4,426.9
9.625	53.5	C-90	LTC	1,399,000	1,157,000	1,157,000	925,600	6,223.1	5,146.6	5,146.6	4,117.3
9.625	53.5	C-90	BTC	1,399,000	1,386,000	1,386,000	1,108,800	6,223.1	6,165.2	6,165.2	4,932.2

Check every figure against your own pipe records before you pull.

Casingjacks

Casingjacks LLC | sales@casingjack.com

Max pull tables

Data version 1.326cfcf0 | Build date 2026-11-17

Max pull

OD in	Weight lb/ft	Grade	Connection	Body lb	Joint lb	Lesser lb	P_allow lb	Body kN	Joint kN	Lesser kN	P_allow kN
9.625	53.5	C-95	LTC	1,477,000	1,220,000	1,220,000	976,000	6,570	5,426.8	5,426.8	4,341.5
9.625	53.5	C-95	BTC	1,477,000	1,458,000	1,458,000	1,166,400	6,570	6,485.5	6,485.5	5,188.4
9.625	53.5	T-95	LTC	1,477,000	1,220,000	1,220,000	976,000	6,570	5,426.8	5,426.8	4,341.5
9.625	53.5	T-95	BTC	1,477,000	1,458,000	1,458,000	1,166,400	6,570	6,485.5	6,485.5	5,188.4
9.625	53.5	P-110	LTC	1,710,000	1,422,000	1,422,000	1,137,600	7,606.5	6,325.4	6,325.4	5,060.3
9.625	53.5	P-110	BTC	1,710,000	1,718,000	1,710,000	1,368,000	7,606.5	7,642	7,606.5	6,085.2
9.625	53.5	Q-125	LTC	1,943,000	1,595,000	1,595,000	1,276,000	8,642.9	7,094.9	7,094.9	5,675.9
9.625	53.5	Q-125	BTC	1,943,000	1,890,000	1,890,000	1,512,000	8,642.9	8,407.1	8,407.1	6,725.7
9.625	58.4	L-80	LTC	1,350,000	1,151,000	1,151,000	920,800	6,005.1	5,119.9	5,119.9	4,095.9
9.625	58.4	L-80	BTC	1,350,000	1,396,000	1,350,000	1,080,000	6,005.1	6,209.7	6,005.1	4,804.1
9.625	58.4	N-80	LTC	1,350,000	1,167,000	1,167,000	933,600	6,005.1	5,191.1	5,191.1	4,152.9
9.625	58.4	N-80	BTC	1,350,000	1,443,000	1,350,000	1,080,000	6,005.1	6,418.8	6,005.1	4,804.1
9.625	58.4	C-90	LTC	1,519,000	1,272,000	1,272,000	1,017,600	6,756.8	5,658.1	5,658.1	4,526.5
9.625	58.4	C-90	BTC	1,519,000	1,504,000	1,504,000	1,203,200	6,756.8	6,690.1	6,690.1	5,352.1
9.625	58.4	C-95	LTC	1,604,000	1,341,000	1,341,000	1,072,800	7,134.9	5,965.1	5,965.1	4,772.1
9.625	58.4	C-95	BTC	1,604,000	1,583,000	1,583,000	1,266,400	7,134.9	7,041.5	7,041.5	5,633.2
9.625	58.4	T-95	LTC	1,604,000	1,341,000	1,341,000	1,072,800	7,134.9	5,965.1	5,965.1	4,772.1
9.625	58.4	T-95	BTC	1,604,000	1,583,000	1,583,000	1,266,400	7,134.9	7,041.5	7,041.5	5,633.2
9.625	58.4	P-110	LTC	1,857,000	1,564,000	1,564,000	1,251,200	8,260.3	6,957	6,957	5,565.6
9.625	58.4	P-110	BTC	1,857,000	1,865,000	1,857,000	1,485,600	8,260.3	8,295.9	8,260.3	6,608.3
9.625	58.4	Q-125	LTC	2,110,000	1,754,000	1,754,000	1,403,200	9,385.7	7,802.2	7,802.2	6,241.7
9.625	58.4	Q-125	BTC	2,110,000	2,052,000	2,052,000	1,641,600	9,385.7	9,127.8	9,127.8	7,302.2
9.625	59.4	C-90	Body only	1,553,000	Not recorded	1,553,000	1,242,400	6,908.1	Not recorded	6,908.1	5,526.5
9.625	59.4	T-95	Body only	1,634,000	Not recorded	1,634,000	1,307,200	7,268.4	Not recorded	7,268.4	5,814.7
9.625	64.9	C-90	Body only	1,701,000	Not recorded	1,701,000	1,360,800	7,566.4	Not recorded	7,566.4	6,053.1

Check every figure against your own pipe records before you pull.

Casingjacks

Casingjacks LLC | sales@casingjack.com

Max pull tables

Data version 1.326cfcf0 | Build date 2026-11-17

Max pull

OD in	Weight lb/ft	Grade	Connection	Body lb	Joint lb	Lesser lb	P_allow lb	Body kN	Joint kN	Lesser kN	P_allow kN
9.625	64.9	T-95	Body only	1,796,000	Not recorded	1,796,000	1,436,800	7,989	Not recorded	7,989	6,391.2
9.625	70.3	C-90	Body only	1,845,000	Not recorded	1,845,000	1,476,000	8,207	Not recorded	8,207	6,565.6
9.625	70.3	T-95	Body only	1,948,000	Not recorded	1,948,000	1,558,400	8,665.1	Not recorded	8,665.1	6,932.1
9.625	75.6	C-90	Body only	1,989,000	Not recorded	1,989,000	1,591,200	8,847.5	Not recorded	8,847.5	7,078
9.625	75.6	T-95	Body only	2,100,000	Not recorded	2,100,000	1,680,000	9,341.3	Not recorded	9,341.3	7,473
9.75	59.2	P-110	LTC	1,882,000	1,387,000	1,387,000	1,109,600	8,371.6	6,169.7	6,169.7	4,935.7
9.75	59.2	P-110	BTC	1,882,000	1,681,000	1,681,000	1,344,800	8,371.6	7,477.5	7,477.5	5,982
9.75	59.2	Q-125	LTC	2,139,000	1,555,000	1,555,000	1,244,000	9,514.7	6,917	6,917	5,533.6
9.75	59.2	Q-125	BTC	2,139,000	1,850,000	1,850,000	1,480,000	9,514.7	8,229.2	8,229.2	6,583.4
9.875	62.8	P-110	LTC	1,998,000	1,294,000	1,294,000	1,035,200	8,887.5	5,756	5,756	4,604.8
9.875	62.8	P-110	BTC	1,998,000	1,584,000	1,584,000	1,267,200	8,887.5	7,046	7,046	5,636.8
9.875	62.8	Q-125	LTC	2,270,000	1,451,000	1,451,000	1,160,800	10,097.5	6,454.4	6,454.4	5,163.5
9.875	62.8	Q-125	BTC	2,270,000	1,743,000	1,743,000	1,394,400	10,097.5	7,753.3	7,753.3	6,202.6
10.75	32.75	H-40	STC	367,000	205,000	205,000	164,000	1,632.5	911.9	911.9	729.5
10.75	40.5	H-40	STC	457,000	314,000	314,000	251,200	2,032.8	1,396.7	1,396.7	1,117.4
10.75	40.5	J-55	STC	629,000	420,000	420,000	336,000	2,797.9	1,868.3	1,868.3	1,494.6
10.75	40.5	J-55	BTC	629,000	700,000	629,000	503,200	2,797.9	3,113.8	2,797.9	2,238.3
10.75	40.5	K-55	STC	629,000	450,000	450,000	360,000	2,797.9	2,001.7	2,001.7	1,601.4
10.75	40.5	K-55	BTC	629,000	819,000	629,000	503,200	2,797.9	3,643.1	2,797.9	2,238.3
10.75	40.5	M-65	STC	743,000	491,000	491,000	392,800	3,305	2,184.1	2,184.1	1,747.3
10.75	40.5	M-65	BTC	743,000	806,000	743,000	594,400	3,305	3,585.3	3,305	2,644
10.75	40.5	N-80	STC	915,000	597,000	597,000	477,600	4,070.1	2,655.6	2,655.6	2,124.5
10.75	40.5	N-80	BTC	915,000	964,000	915,000	732,000	4,070.1	4,288.1	4,070.1	3,256.1
10.75	45.5	J-55	STC	715,000	493,000	493,000	394,400	3,180.5	2,193	2,193	1,754.4
10.75	45.5	J-55	BTC	715,000	796,000	715,000	572,000	3,180.5	3,540.8	3,180.5	2,544.4

Check every figure against your own pipe records before you pull.

Casingjacks

Casingjacks LLC | sales@casingjack.com

Max pull tables

Data version 1.326cfcf0 | Build date 2026-11-17

Max pull

OD in	Weight lb/ft	Grade	Connection	Body lb	Joint lb	Lesser lb	P_allow lb	Body kN	Joint kN	Lesser kN	P_allow kN
10.75	45.5	M-65	STC	845,000	576,000	576,000	460,800	3,758.7	2,562.2	2,562.2	2,049.7
10.75	45.5	M-65	BTC	845,000	916,000	845,000	676,000	3,758.7	4,074.6	3,758.7	3,007
10.75	45.5	N-80	STC	1,040,000	701,000	701,000	560,800	4,626.2	3,118.2	3,118.2	2,494.6
10.75	45.5	N-80	BTC	1,040,000	1,097,000	1,040,000	832,000	4,626.2	4,879.7	4,626.2	3,700.9
10.75	51	J-55	STC	801,000	565,000	565,000	452,000	3,563	2,513.2	2,513.2	2,010.6
10.75	51	J-55	BTC	801,000	891,000	801,000	640,800	3,563	3,963.4	3,563	2,850.4
10.75	51	K-55	STC	801,000	606,000	606,000	484,800	3,563	2,695.6	2,695.6	2,156.5
10.75	51	K-55	BTC	801,000	1,043,000	801,000	640,800	3,563	4,639.5	3,563	2,850.4
10.75	51	M-65	STC	946,000	661,000	661,000	528,800	4,208	2,940.3	2,940.3	2,352.2
10.75	51	M-65	BTC	946,000	1,026,000	946,000	756,800	4,208	4,563.9	4,208	3,366.4
10.75	51	L-80	STC	1,165,000	794,000	794,000	635,200	5,182.2	3,531.9	3,531.9	2,825.5
10.75	51	L-80	BTC	1,165,000	1,190,000	1,165,000	932,000	5,182.2	5,293.4	5,182.2	4,145.7
10.75	51	N-80	STC	1,165,000	804,000	804,000	643,200	5,182.2	3,576.4	3,576.4	2,861.1
10.75	51	N-80	BTC	1,165,000	1,228,000	1,165,000	932,000	5,182.2	5,462.4	5,182.2	4,145.7
10.75	51	C-90	STC	1,311,000	879,000	879,000	703,200	5,831.6	3,910	3,910	3,128
10.75	51	C-90	BTC	1,311,000	1,287,000	1,287,000	1,029,600	5,831.6	5,724.9	5,724.9	4,579.9
10.75	51	C-95	STC	1,383,000	927,000	927,000	741,600	6,151.9	4,123.5	4,123.5	3,298.8
10.75	51	C-95	BTC	1,383,000	1,354,000	1,354,000	1,083,200	6,151.9	6,022.9	6,022.9	4,818.3
10.75	51	T-95	STC	1,383,000	927,000	927,000	741,600	6,151.9	4,123.5	4,123.5	3,298.8
10.75	51	T-95	BTC	1,383,000	1,354,000	1,354,000	1,083,200	6,151.9	6,022.9	6,022.9	4,818.3
10.75	51	P-110	STC	1,602,000	1,080,000	1,080,000	864,000	7,126.1	4,804.1	4,804.1	3,843.3
10.75	51	P-110	BTC	1,602,000	1,594,000	1,594,000	1,275,200	7,126.1	7,090.5	7,090.5	5,672.4
10.75	51	Q-125	STC	1,820,000	1,213,000	1,213,000	970,400	8,095.8	5,395.7	5,395.7	4,316.6
10.75	51	Q-125	BTC	1,820,000	1,758,000	1,758,000	1,406,400	8,095.8	7,820	7,820	6,256
10.75	55.5	L-80	STC	1,276,000	884,000	884,000	707,200	5,675.9	3,932.2	3,932.2	3,145.8

Check every figure against your own pipe records before you pull.

Casingjacks

Casingjacks LLC | sales@casingjack.com

Max pull tables

Data version 1.326cfcf0 | Build date 2026-11-17

`Max pull`

OD in	Weight lb/ft	Grade	Connection	Body lb	Joint lb	Lesser lb	P_allow lb	Body kN	Joint kN	Lesser kN	P_allow kN
10.75	55.5	L-80	BTC	1,276,000	1,303,000	1,276,000	1,020,800	5,675.9	5,796	5,675.9	4,540.7
10.75	55.5	N-80	STC	1,276,000	895,000	895,000	716,000	5,675.9	3,981.2	3,981.2	3,184.9
10.75	55.5	N-80	BTC	1,276,000	1,345,000	1,276,000	1,020,800	5,675.9	5,982.9	5,675.9	4,540.7
10.75	55.5	C-90	STC	1,435,000	979,000	979,000	783,200	6,383.2	4,354.8	4,354.8	3,483.8
10.75	55.5	C-90	BTC	1,435,000	1,409,000	1,409,000	1,127,200	6,383.2	6,267.5	6,267.5	5,014
10.75	55.5	C-95	STC	1,515,000	1,032,000	1,032,000	825,600	6,739.1	4,590.6	4,590.6	3,672.5
10.75	55.5	C-95	BTC	1,515,000	1,483,000	1,483,000	1,186,400	6,739.1	6,596.7	6,596.7	5,277.4
10.75	55.5	T-95	STC	1,515,000	1,032,000	1,032,000	825,600	6,739.1	4,590.6	4,590.6	3,672.5
10.75	55.5	T-95	BTC	1,515,000	1,483,000	1,483,000	1,186,400	6,739.1	6,596.7	6,596.7	5,277.4
10.75	55.5	P-110	STC	1,754,000	1,203,000	1,203,000	962,400	7,802.2	5,351.2	5,351.2	4,281
10.75	55.5	P-110	BTC	1,754,000	1,745,000	1,745,000	1,396,000	7,802.2	7,762.1	7,762.1	6,209.7
10.75	55.5	Q-125	STC	1,993,000	1,351,000	1,351,000	1,080,800	8,865.3	6,009.5	6,009.5	4,807.6
10.75	55.5	Q-125	BTC	1,993,000	1,925,000	1,925,000	1,540,000	8,865.3	8,562.8	8,562.8	6,850.3
10.75	60.7	L-80	STC	1,398,000	983,000	983,000	786,400	6,218.6	4,372.6	4,372.6	3,498.1
10.75	60.7	L-80	BTC	1,398,000	1,428,000	1,398,000	1,118,400	6,218.6	6,352.1	6,218.6	4,974.9
10.75	60.7	N-80	STC	1,398,000	996,000	996,000	796,800	6,218.6	4,430.4	4,430.4	3,544.3
10.75	60.7	N-80	BTC	1,398,000	1,473,000	1,398,000	1,118,400	6,218.6	6,552.2	6,218.6	4,974.9
10.75	60.7	C-90	STC	1,573,000	1,089,000	1,089,000	871,200	6,997.1	4,844.1	4,844.1	3,875.3
10.75	60.7	C-90	BTC	1,573,000	1,544,000	1,544,000	1,235,200	6,997.1	6,868.1	6,868.1	5,494.4
10.75	60.7	C-95	STC	1,660,000	1,148,000	1,148,000	918,400	7,384	5,106.6	5,106.6	4,085.2
10.75	60.7	C-95	BTC	1,660,000	1,625,000	1,625,000	1,300,000	7,384	7,228.4	7,228.4	5,782.7
10.75	60.7	T-95	STC	1,660,000	1,148,000	1,148,000	918,400	7,384	5,106.6	5,106.6	4,085.2
10.75	60.7	T-95	BTC	1,660,000	1,625,000	1,625,000	1,300,000	7,384	7,228.4	7,228.4	5,782.7
10.75	60.7	P-110	STC	1,922,000	1,338,000	1,338,000	1,070,400	8,549.5	5,951.7	5,951.7	4,761.4
10.75	60.7	P-110	BTC	1,922,000	1,912,000	1,912,000	1,529,600	8,549.5	8,505	8,505	6,804

Check every figure against your own pipe records before you pull.

Casingjacks

Casingjacks LLC | sales@casingjack.com

Max pull tables

Data version 1.326cfcf0 | Build date 2026-11-17

Max pull

OD in	Weight lb/ft	Grade	Connection	Body lb	Joint lb	Lesser lb	P_allow lb	Body kN	Joint kN	Lesser kN	P_allow kN
10.75	60.7	Q-125	STC	2,184,000	1,503,000	1,503,000	1,202,400	9,714.9	6,685.7	6,685.7	5,348.5
10.75	60.7	Q-125	BTC	2,184,000	2,109,000	2,109,000	1,687,200	9,714.9	9,381.3	9,381.3	7,505
10.75	65.7	L-80	STC	1,519,000	1,082,000	1,082,000	865,600	6,756.8	4,813	4,813	3,850.4
10.75	65.7	L-80	BTC	1,519,000	1,551,000	1,519,000	1,215,200	6,756.8	6,899.2	6,756.8	5,405.5
10.75	65.7	N-80	STC	1,519,000	1,096,000	1,096,000	876,800	6,756.8	4,875.3	4,875.3	3,900.2
10.75	65.7	N-80	BTC	1,519,000	1,600,000	1,519,000	1,215,200	6,756.8	7,117.2	6,756.8	5,405.5
10.75	65.7	C-90	STC	1,708,000	1,198,000	1,198,000	958,400	7,597.6	5,329	5,329	4,263.2
10.75	65.7	C-90	BTC	1,708,000	1,677,000	1,677,000	1,341,600	7,597.6	7,459.7	7,459.7	5,967.7
10.75	65.7	T-95	STC	1,803,000	1,263,000	1,263,000	1,010,400	8,020.1	5,618.1	5,618.1	4,494.5
10.75	65.7	T-95	BTC	1,803,000	1,765,000	1,765,000	1,412,000	8,020.1	7,851.1	7,851.1	6,280.9
10.75	65.7	P-110	STC	2,088,000	1,472,000	1,472,000	1,177,600	9,287.9	6,547.8	6,547.8	5,238.2
10.75	65.7	P-110	BTC	2,088,000	2,077,000	2,077,000	1,661,600	9,287.9	9,239	9,239	7,391.2
10.75	65.7	Q-125	STC	2,373,000	1,653,000	1,653,000	1,322,400	10,555.6	7,352.9	7,352.9	5,882.3
10.75	65.7	Q-125	BTC	2,373,000	2,291,000	2,291,000	1,832,800	10,555.6	10,190.9	10,190.9	8,152.7
10.75	71.1	P-110	STC	2,269,000	1,618,000	1,618,000	1,294,400	10,093	7,197.2	7,197.2	5,757.8
10.75	71.1	P-110	BTC	2,269,000	2,257,000	2,257,000	1,805,600	10,093	10,039.6	10,039.6	8,031.7
10.75	71.1	Q-125	STC	2,578,000	1,817,000	1,817,000	1,453,600	11,467.5	8,082.4	8,082.4	6,465.9
10.75	71.1	Q-125	BTC	2,578,000	2,489,000	2,489,000	1,991,200	11,467.5	11,071.6	11,071.6	8,857.3
10.75	73.2	C-90	Body only	1,915,000	Not recorded	1,915,000	1,532,000	8,518.3	Not recorded	8,518.3	6,814.7
10.75	73.2	T-95	Body only	2,021,000	Not recorded	2,021,000	1,616,800	8,989.9	Not recorded	8,989.9	7,191.9
10.75	79.2	C-90	Body only	2,079,000	Not recorded	2,079,000	1,663,200	9,247.9	Not recorded	9,247.9	7,398.3
10.75	79.2	T-95	Body only	2,194,000	Not recorded	2,194,000	1,755,200	9,759.4	Not recorded	9,759.4	7,807.5
10.75	85.3	C-90	Body only	2,243,000	Not recorded	2,243,000	1,794,400	9,977.4	Not recorded	9,977.4	7,981.9
10.75	85.3	T-95	Body only	2,367,000	Not recorded	2,367,000	1,893,600	10,528.9	Not recorded	10,528.9	8,423.2
11.75	42	H-40	STC	478,000	307,000	307,000	245,600	2,126.2	1,365.6	1,365.6	1,092.5

Check every figure against your own pipe records before you pull.

Casingjacks

Casingjacks LLC | sales@casingjack.com

Max pull tables

Data version 1.326cfcf0 | Build date 2026-11-17

Max pull

OD in	Weight lb/ft	Grade	Connection	Body lb	Joint lb	Lesser lb	P_allow lb	Body kN	Joint kN	Lesser kN	P_allow kN
11.75	42	H-40	BTC	478,000	554,000	478,000	382,400	2,126.2	2,464.3	2,126.2	1,701
11.75	47	J-55	STC	737,000	477,000	477,000	381,600	3,278.3	2,121.8	2,121.8	1,697.4
11.75	47	J-55	BTC	737,000	807,000	737,000	589,600	3,278.3	3,589.7	3,278.3	2,622.7
11.75	47	K-55	STC	737,000	509,000	509,000	407,200	3,278.3	2,264.1	2,264.1	1,811.3
11.75	47	K-55	BTC	737,000	935,000	737,000	589,600	3,278.3	4,159.1	3,278.3	2,622.7
11.75	47	M-65	STC	871,000	557,000	557,000	445,600	3,874.4	2,477.7	2,477.7	1,982.1
11.75	47	M-65	BTC	871,000	931,000	871,000	696,800	3,874.4	4,141.3	3,874.4	3,099.5
11.75	54	J-55	STC	850,000	568,000	568,000	454,400	3,781	2,526.6	2,526.6	2,021.3
11.75	54	J-55	BTC	850,000	931,000	850,000	680,000	3,781	4,141.3	3,781	3,024.8
11.75	54	K-55	STC	850,000	606,000	606,000	484,800	3,781	2,695.6	2,695.6	2,156.5
11.75	54	K-55	BTC	850,000	1,079,000	850,000	680,000	3,781	4,799.6	3,781	3,024.8
11.75	54	M-65	STC	1,005,000	665,000	665,000	532,000	4,470.5	2,958.1	2,958.1	2,366.5
11.75	54	M-65	BTC	1,005,000	1,074,000	1,005,000	804,000	4,470.5	4,777.4	4,470.5	3,576.4
11.75	60	J-55	STC	952,000	649,000	649,000	519,200	4,234.7	2,886.9	2,886.9	2,309.5
11.75	60	J-55	BTC	952,000	1,042,000	952,000	761,600	4,234.7	4,635	4,234.7	3,387.8
11.75	60	K-55	STC	952,000	693,000	693,000	554,400	4,234.7	3,082.6	3,082.6	2,466.1
11.75	60	K-55	BTC	952,000	1,208,000	952,000	761,600	4,234.7	5,373.5	4,234.7	3,387.8
11.75	60	M-65	STC	1,125,000	759,000	759,000	607,200	5,004.2	3,376.2	3,376.2	2,701
11.75	60	M-65	BTC	1,125,000	1,201,000	1,125,000	900,000	5,004.2	5,342.3	5,004.2	4,003.4
11.75	60	L-80	STC	1,384,000	913,000	913,000	730,400	6,156.3	4,061.2	4,061.2	3,249
11.75	60	L-80	BTC	1,384,000	1,399,000	1,384,000	1,107,200	6,156.3	6,223.1	6,156.3	4,925.1
11.75	60	N-80	STC	1,384,000	924,000	924,000	739,200	6,156.3	4,110.2	4,110.2	3,288.1
11.75	60	N-80	BTC	1,384,000	1,440,000	1,384,000	1,107,200	6,156.3	6,405.4	6,156.3	4,925.1
11.75	60	C-90	STC	1,557,000	1,011,000	1,011,000	808,800	6,925.9	4,497.2	4,497.2	3,597.7
11.75	60	C-90	BTC	1,557,000	1,517,000	1,517,000	1,213,600	6,925.9	6,748	6,748	5,398.4

Check every figure against your own pipe records before you pull.

Casingjacks

Casingjacks LLC | sales@casingjack.com

Max pull tables

Data version 1.326cfcf0 | Build date 2026-11-17

Max pull

OD in	Weight lb/ft	Grade	Connection	Body lb	Joint lb	Lesser lb	P_allow lb	Body kN	Joint kN	Lesser kN	P_allow kN
11.75	60	C-95	STC	1,644,000	1,066,000	1,066,000	852,800	7,312.9	4,741.8	4,741.8	3,793.4
11.75	60	C-95	BTC	1,644,000	1,596,000	1,596,000	1,276,800	7,312.9	7,099.4	7,099.4	5,679.5
11.75	60	T-95	STC	1,644,000	1,066,000	1,066,000	852,800	7,312.9	4,741.8	4,741.8	3,793.4
11.75	60	T-95	BTC	1,644,000	1,596,000	1,596,000	1,276,800	7,312.9	7,099.4	7,099.4	5,679.5
11.75	60	P-110	STC	1,903,000	1,242,000	1,242,000	993,600	8,465	5,524.7	5,524.7	4,419.8
11.75	60	P-110	BTC	1,903,000	1,877,000	1,877,000	1,501,600	8,465	8,349.3	8,349.3	6,679.4
11.75	60	Q-125	STC	2,163,000	1,396,000	1,396,000	1,116,800	9,621.5	6,209.7	6,209.7	4,967.8
11.75	60	Q-125	BTC	2,163,000	2,074,000	2,074,000	1,659,200	9,621.5	9,225.6	9,225.6	7,380.5
11.75	65	M-65	STC	1,223,000	837,000	837,000	669,600	5,440.2	3,723.2	3,723.2	2,978.5
11.75	65	M-65	BTC	1,223,000	1,307,000	1,223,000	978,400	5,440.2	5,813.8	5,440.2	4,352.1
11.75	65	L-80	STC	1,505,000	1,007,000	1,007,000	805,600	6,694.6	4,479.4	4,479.4	3,583.5
11.75	65	L-80	BTC	1,505,000	1,521,000	1,505,000	1,204,000	6,694.6	6,765.7	6,694.6	5,355.7
11.75	65	N-80	STC	1,505,000	1,019,000	1,019,000	815,200	6,694.6	4,532.7	4,532.7	3,626.2
11.75	65	N-80	BTC	1,505,000	1,566,000	1,505,000	1,204,000	6,694.6	6,965.9	6,694.6	5,355.7
11.75	65	P-110	STC	2,070,000	1,371,000	1,371,000	1,096,800	9,207.8	6,098.5	6,098.5	4,878.8
11.75	65	P-110	BTC	2,070,000	2,041,000	2,041,000	1,632,800	9,207.8	9,078.8	9,078.8	7,263.1
11.75	65	Q-125	STC	2,352,000	1,540,000	1,540,000	1,232,000	10,462.2	6,850.3	6,850.3	5,480.2
11.75	65	Q-125	BTC	2,352,000	2,256,000	2,256,000	1,804,800	10,462.2	10,035.2	10,035.2	8,028.2
11.75	71	Q-125	STC	2,552,000	1,693,000	1,693,000	1,354,400	11,351.9	7,530.8	7,530.8	6,024.7
11.75	71	Q-125	BTC	2,552,000	2,448,000	2,448,000	1,958,400	11,351.9	10,889.2	10,889.2	8,711.4
11.875	71.8	P-110	STC	2,271,000	1,329,000	1,329,000	1,063,200	10,101.9	5,911.7	5,911.7	4,729.3
11.875	71.8	P-110	BTC	2,271,000	1,988,000	1,988,000	1,590,400	10,101.9	8,843.1	8,843.1	7,074.5
11.875	71.8	Q-125	STC	2,581,000	1,494,000	1,494,000	1,195,200	11,480.9	6,645.6	6,645.6	5,316.5
11.875	71.8	Q-125	BTC	2,581,000	2,198,000	2,198,000	1,758,400	11,480.9	9,777.2	9,777.2	7,821.8
13.375	48	H-40	STC	541,000	322,000	322,000	257,600	2,406.5	1,432.3	1,432.3	1,145.9

Check every figure against your own pipe records before you pull.

Casingjacks

Casingjacks LLC | sales@casingjack.com

Max pull tables

Data version 1.326cfcf0 | Build date 2026-11-17

Max pull

OD in	Weight lb/ft	Grade	Connection	Body lb	Joint lb	Lesser lb	P_allow lb	Body kN	Joint kN	Lesser kN	P_allow kN
13.375	48	H-40	BTC	541,000	607,000	541,000	432,800	2,406.5	2,700.1	2,406.5	1,925.2
13.375	54.5	J-55	STC	853,000	514,000	514,000	411,200	3,794.3	2,286.4	2,286.4	1,829.1
13.375	54.5	J-55	BTC	853,000	909,000	853,000	682,400	3,794.3	4,043.4	3,794.3	3,035.5
13.375	54.5	K-55	STC	853,000	547,000	547,000	437,600	3,794.3	2,433.2	2,433.2	1,946.5
13.375	54.5	K-55	BTC	853,000	1,038,000	853,000	682,400	3,794.3	4,617.3	3,794.3	3,035.5
13.375	54.5	M-65	STC	1,008,000	602,000	602,000	481,600	4,483.8	2,677.8	2,677.8	2,142.3
13.375	54.5	M-65	BTC	1,008,000	1,052,000	1,008,000	806,400	4,483.8	4,679.5	4,483.8	3,587
13.375	61	J-55	STC	962,000	595,000	595,000	476,000	4,279.2	2,646.7	2,646.7	2,117.4
13.375	61	J-55	BTC	962,000	1,025,000	962,000	769,600	4,279.2	4,559.4	4,279.2	3,423.4
13.375	61	K-55	STC	962,000	633,000	633,000	506,400	4,279.2	2,815.7	2,815.7	2,252.6
13.375	61	K-55	BTC	962,000	1,169,000	962,000	769,600	4,279.2	5,200	4,279.2	3,423.4
13.375	61	M-65	STC	1,137,000	697,000	697,000	557,600	5,057.6	3,100.4	3,100.4	2,480.3
13.375	61	M-65	BTC	1,137,000	1,185,000	1,137,000	909,600	5,057.6	5,271.1	5,057.6	4,046.1
13.375	68	J-55	STC	1,069,000	675,000	675,000	540,000	4,755.1	3,002.5	3,002.5	2,402
13.375	68	J-55	BTC	1,069,000	1,140,000	1,069,000	855,200	4,755.1	5,071	4,755.1	3,804.1
13.375	68	K-55	STC	1,069,000	718,000	718,000	574,400	4,755.1	3,193.8	3,193.8	2,555.1
13.375	68	K-55	BTC	1,069,000	1,300,000	1,069,000	855,200	4,755.1	5,782.7	4,755.1	3,804.1
13.375	68	M-65	STC	1,264,000	791,000	791,000	632,800	5,622.6	3,518.5	3,518.5	2,814.8
13.375	68	M-65	BTC	1,264,000	1,318,000	1,264,000	1,011,200	5,622.6	5,862.8	5,622.6	4,498
13.375	68	L-80	STC	1,556,000	952,000	952,000	761,600	6,921.4	4,234.7	4,234.7	3,387.8
13.375	68	L-80	BTC	1,556,000	1,545,000	1,545,000	1,236,000	6,921.4	6,872.5	6,872.5	5,498
13.375	68	N-80	STC	1,556,000	963,000	963,000	770,400	6,921.4	4,283.6	4,283.6	3,426.9
13.375	68	N-80	BTC	1,556,000	1,585,000	1,556,000	1,244,800	6,921.4	7,050.4	6,921.4	5,537.1
13.375	68	C-90	STC	1,750,000	1,057,000	1,057,000	845,600	7,784.4	4,701.8	4,701.8	3,761.4
13.375	68	C-90	BTC	1,750,000	1,683,000	1,683,000	1,346,400	7,784.4	7,486.4	7,486.4	5,989.1

Check every figure against your own pipe records before you pull.

Casingjacks

Casingjacks LLC | sales@casingjack.com

Max pull tables

Data version 1.326cfcf0 | Build date 2026-11-17

Max pull

OD in	Weight lb/ft	Grade	Connection	Body lb	Joint lb	Lesser lb	P_allow lb	Body kN	Joint kN	Lesser kN	P_allow kN
13.375	68	C-95	STC	1,847,000	1,114,000	1,114,000	891,200	8,215.9	4,955.3	4,955.3	3,964.3
13.375	68	C-95	BTC	1,847,000	1,772,000	1,772,000	1,417,600	8,215.9	7,882.2	7,882.2	6,305.8
13.375	68	T-95	STC	1,847,000	1,114,000	1,114,000	891,200	8,215.9	4,955.3	4,955.3	3,964.3
13.375	68	T-95	BTC	1,847,000	1,772,000	1,772,000	1,417,600	8,215.9	7,882.2	7,882.2	6,305.8
13.375	68	P-110	STC	2,139,000	1,297,000	1,297,000	1,037,600	9,514.7	5,769.3	5,769.3	4,615.5
13.375	68	P-110	BTC	2,139,000	2,079,000	2,079,000	1,663,200	9,514.7	9,247.9	9,247.9	7,398.3
13.375	72	M-65	STC	1,350,000	854,000	854,000	683,200	6,005.1	3,798.8	3,798.8	3,039
13.375	72	M-65	BTC	1,350,000	1,408,000	1,350,000	1,080,000	6,005.1	6,263.1	6,005.1	4,804.1
13.375	72	L-80	STC	1,661,000	1,029,000	1,029,000	823,200	7,388.5	4,577.2	4,577.2	3,661.8
13.375	72	L-80	BTC	1,661,000	1,650,000	1,650,000	1,320,000	7,388.5	7,339.6	7,339.6	5,871.7
13.375	72	N-80	STC	1,661,000	1,040,000	1,040,000	832,000	7,388.5	4,626.2	4,626.2	3,700.9
13.375	72	N-80	BTC	1,661,000	1,693,000	1,661,000	1,328,800	7,388.5	7,530.8	7,388.5	5,910.8
13.375	72	C-90	STC	1,869,000	1,142,000	1,142,000	913,600	8,313.7	5,079.9	5,079.9	4,063.9
13.375	72	C-90	BTC	1,869,000	1,798,000	1,798,000	1,438,400	8,313.7	7,997.9	7,997.9	6,398.3
13.375	72	C-95	STC	1,973,000	1,204,000	1,204,000	963,200	8,776.3	5,355.7	5,355.7	4,284.5
13.375	72	C-95	BTC	1,973,000	1,893,000	1,893,000	1,514,400	8,776.3	8,420.5	8,420.5	6,736.4
13.375	72	T-95	STC	1,973,000	1,204,000	1,204,000	963,200	8,776.3	5,355.7	5,355.7	4,284.5
13.375	72	T-95	BTC	1,973,000	1,893,000	1,893,000	1,514,400	8,776.3	8,420.5	8,420.5	6,736.4
13.375	72	P-110	STC	2,284,000	1,402,000	1,402,000	1,121,600	10,159.7	6,236.4	6,236.4	4,989.1
13.375	72	P-110	BTC	2,284,000	2,221,000	2,221,000	1,776,800	10,159.7	9,879.5	9,879.5	7,903.6
13.375	72	Q-125	STC	2,596,000	1,577,000	1,577,000	1,261,600	11,547.6	7,014.8	7,014.8	5,611.9
13.375	72	Q-125	BTC	2,596,000	2,463,000	2,463,000	1,970,400	11,547.6	10,956	10,956	8,764.8
13.375	80.7	P-110	BTC	2,565,000	2,493,000	2,493,000	1,994,400	11,409.7	11,089.4	11,089.4	8,871.5
13.375	80.7	Q-125	BTC	2,914,000	2,765,000	2,765,000	2,212,000	12,962.1	12,299.3	12,299.3	9,839.5
13.375	86	P-110	BTC	2,754,000	2,677,000	2,677,000	2,141,600	12,250.4	11,907.9	11,907.9	9,526.3

Check every figure against your own pipe records before you pull.

Casingjacks

Casingjacks LLC | sales@casingjack.com

Max pull tables

Data version 1.326cfcf0 | Build date 2026-11-17

Max pull

OD in	Weight lb/ft	Grade	Connection	Body lb	Joint lb	Lesser lb	P_allow lb	Body kN	Joint kN	Lesser kN	P_allow kN
13.375	86	Q-125	BTC	3,129,000	2,969,000	2,969,000	2,375,200	13,918.5	13,206.8	13,206.8	10,565.4
13.5	81.4	P-110	BTC	2,590,000	2,235,000	2,235,000	1,788,000	11,520.9	9,941.8	9,941.8	7,953.4
13.5	81.4	Q-125	BTC	2,943,000	2,479,000	2,479,000	1,983,200	13,091.1	11,027.1	11,027.1	8,821.7
13.625	88.2	P-110	BTC	2,808,000	2,163,000	2,163,000	1,730,400	12,490.6	9,621.5	9,621.5	7,697.2
13.625	88.2	Q-125	BTC	3,191,000	2,399,000	2,399,000	1,919,200	14,194.3	10,671.3	10,671.3	8,537
16	65	H-40	STC	736,000	439,000	439,000	351,200	3,273.9	1,952.8	1,952.8	1,562.2
16	65	H-40	BTC	736,000	781,000	736,000	588,800	3,273.9	3,474.1	3,273.9	2,619.1
16	75	J-55	STC	1,178,000	710,000	710,000	568,000	5,240	3,158.2	3,158.2	2,526.6
16	75	J-55	BTC	1,178,000	1,200,000	1,178,000	942,400	5,240	5,337.9	5,240	4,192
16	75	K-55	STC	1,178,000	752,000	752,000	601,600	5,240	3,345.1	3,345.1	2,676.1
16	75	K-55	BTC	1,178,000	1,331,000	1,178,000	942,400	5,240	5,920.6	5,240	4,192
16	75	M-65	STC	1,392,000	832,000	832,000	665,600	6,191.9	3,700.9	3,700.9	2,960.7
16	75	M-65	BTC	1,392,000	1,394,000	1,392,000	1,113,600	6,191.9	6,200.8	6,191.9	4,953.5
16	84	J-55	STC	1,326,000	817,000	817,000	653,600	5,898.3	3,634.2	3,634.2	2,907.4
16	84	J-55	BTC	1,326,000	1,351,000	1,326,000	1,060,800	5,898.3	6,009.5	5,898.3	4,718.7
16	84	K-55	STC	1,326,000	865,000	865,000	692,000	5,898.3	3,847.7	3,847.7	3,078.2
16	84	K-55	BTC	1,326,000	1,499,000	1,326,000	1,060,800	5,898.3	6,667.9	5,898.3	4,718.7
16	84	M-65	STC	1,567,000	957,000	957,000	765,600	6,970.4	4,256.9	4,256.9	3,405.6
16	84	M-65	BTC	1,567,000	1,570,000	1,567,000	1,253,600	6,970.4	6,983.7	6,970.4	5,576.3
16	84	N-80	STC	1,929,000	1,167,000	1,167,000	933,600	8,580.6	5,191.1	5,191.1	4,152.9
16	84	N-80	BTC	1,929,000	1,898,000	1,898,000	1,518,400	8,580.6	8,442.7	8,442.7	6,754.2
16	84	P-110	STC	2,652,000	1,575,000	1,575,000	1,260,000	11,796.7	7,005.9	7,005.9	5,604.8
16	84	P-110	BTC	2,652,000	2,518,000	2,518,000	2,014,400	11,796.7	11,200.6	11,200.6	8,960.5
16	84	Q-125	STC	3,014,000	1,773,000	1,773,000	1,418,400	13,406.9	7,886.7	7,886.7	6,309.4
16	84	Q-125	BTC	3,014,000	2,809,000	2,809,000	2,247,200	13,406.9	12,495.1	12,495.1	9,996

Check every figure against your own pipe records before you pull.

Casingjacks

Casingjacks LLC | sales@casingjack.com

Max pull tables

Data version 1.326cfcf0 | Build date 2026-11-17

Max pull

OD in	Weight lb/ft	Grade	Connection	Body lb	Joint lb	Lesser lb	P_allow lb	Body kN	Joint kN	Lesser kN	P_allow kN
16	95	N-80	BTC	2,196,000	2,161,000	2,161,000	1,728,800	9,768.3	9,612.6	9,612.6	7,690.1
16	95	P-110	BTC	3,019,000	2,866,000	2,866,000	2,292,800	13,429.2	12,748.6	12,748.6	10,198.9
16	95	Q-125	BTC	3,431,000	3,198,000	3,198,000	2,558,400	15,261.8	14,225.4	14,225.4	11,380.3
16	97	N-80	BTC	2,230,000	2,194,000	2,194,000	1,755,200	9,919.5	9,759.4	9,759.4	7,807.5
16	97	P-110	BTC	3,067,000	2,910,000	2,910,000	2,328,000	13,642.7	12,944.3	12,944.3	10,355.5
16	97	Q-125	BTC	3,485,000	3,246,000	3,246,000	2,596,800	15,502.1	14,438.9	14,438.9	11,551.1
16	109	J-55	STC	1,739,000	1,116,000	1,116,000	892,800	7,735.5	4,964.2	4,964.2	3,971.4
16	109	J-55	BTC	1,739,000	1,772,000	1,739,000	1,391,200	7,735.5	7,882.2	7,735.5	6,188.4
16	109	K-55	STC	1,739,000	1,181,000	1,181,000	944,800	7,735.5	5,253.3	5,253.3	4,202.7
16	109	K-55	BTC	1,739,000	1,965,000	1,739,000	1,391,200	7,735.5	8,740.8	7,735.5	6,188.4
16	109	N-80	STC	2,530,000	1,594,000	1,594,000	1,275,200	11,254	7,090.5	7,090.5	5,672.4
16	109	N-80	BTC	2,530,000	2,489,000	2,489,000	1,991,200	11,254	11,071.6	11,071.6	8,857.3
16	118	J-55	STC	1,889,000	1,224,000	1,224,000	979,200	8,402.7	5,444.6	5,444.6	4,355.7
16	118	J-55	BTC	1,889,000	1,924,000	1,889,000	1,511,200	8,402.7	8,558.4	8,402.7	6,722.2
16	118	K-55	STC	1,889,000	1,296,000	1,296,000	1,036,800	8,402.7	5,764.9	5,764.9	4,611.9
16	118	K-55	BTC	1,889,000	2,131,000	1,889,000	1,511,200	8,402.7	9,479.2	8,402.7	6,722.2
16	118	N-80	STC	2,747,000	1,741,000	1,741,000	1,392,800	12,219.3	7,744.4	7,744.4	6,195.5
16	118	N-80	BTC	2,747,000	2,703,000	2,703,000	2,162,400	12,219.3	12,023.5	12,023.5	9,618.8
18.625	87.5	H-40	STC	995,000	559,000	559,000	447,200	4,426	2,486.6	2,486.6	1,989.2
18.625	87.5	H-40	BTC	995,000	993,000	993,000	794,400	4,426	4,417.1	4,417.1	3,533.7
18.625	87.5	J-55	STC	1,368,000	754,000	754,000	603,200	6,085.2	3,354	3,354	2,683.2
18.625	87.5	J-55	BTC	1,368,000	1,329,000	1,329,000	1,063,200	6,085.2	5,911.7	5,911.7	4,729.3
18.625	87.5	K-55	STC	1,368,000	794,000	794,000	635,200	6,085.2	3,531.9	3,531.9	2,825.5
18.625	87.5	K-55	BTC	1,368,000	1,427,000	1,368,000	1,094,400	6,085.2	6,347.6	6,085.2	4,868.1
18.625	87.5	N-80	STC	1,990,000	1,079,000	1,079,000	863,200	8,852	4,799.6	4,799.6	3,839.7

Check every figure against your own pipe records before you pull.

Casingjacks

Casingjacks LLC | sales@casingjack.com

Max pull tables

Data version 1.326cfcf0 | Build date 2026-11-17

Max pull

OD in	Weight lb/ft	Grade	Connection	Body lb	Joint lb	Lesser lb	P_allow lb	Body kN	Joint kN	Lesser kN	P_allow kN
18.625	87.5	N-80	BTC	1,990,000	1,887,000	1,887,000	1,509,600	8,852	8,393.8	8,393.8	6,715
18.625	94.5	H-40	STC	1,068,000	609,000	609,000	487,200	4,750.7	2,709	2,709	2,167.2
18.625	94.5	H-40	BTC	1,068,000	1,067,000	1,067,000	853,600	4,750.7	4,746.3	4,746.3	3,797
18.625	94.5	J-55	STC	1,469,000	821,000	821,000	656,800	6,534.4	3,652	3,652	2,921.6
18.625	94.5	J-55	BTC	1,469,000	1,427,000	1,427,000	1,141,600	6,534.4	6,347.6	6,347.6	5,078.1
18.625	94.5	K-55	STC	1,469,000	865,000	865,000	692,000	6,534.4	3,847.7	3,847.7	3,078.2
18.625	94.5	K-55	BTC	1,469,000	1,533,000	1,469,000	1,175,200	6,534.4	6,819.1	6,534.4	5,227.6
18.625	94.5	N-80	STC	2,137,000	1,174,000	1,174,000	939,200	9,505.8	5,222.2	5,222.2	4,177.8
18.625	94.5	N-80	BTC	2,137,000	2,027,000	2,027,000	1,621,600	9,505.8	9,016.5	9,016.5	7,213.2
18.625	106	J-55	STC	1,661,000	948,000	948,000	758,400	7,388.5	4,216.9	4,216.9	3,373.5
18.625	106	J-55	BTC	1,661,000	1,613,000	1,613,000	1,290,400	7,388.5	7,175	7,175	5,740
18.625	106	K-55	STC	1,661,000	998,000	998,000	798,400	7,388.5	4,439.3	4,439.3	3,551.5
18.625	106	K-55	BTC	1,661,000	1,733,000	1,661,000	1,328,800	7,388.5	7,708.8	7,388.5	5,910.8
18.625	106	N-80	STC	2,416,000	1,356,000	1,356,000	1,084,800	10,746.9	6,031.8	6,031.8	4,825.4
18.625	106	N-80	BTC	2,416,000	2,292,000	2,292,000	1,833,600	10,746.9	10,195.3	10,195.3	8,156.3
18.625	117.5	J-55	STC	1,849,000	1,072,000	1,072,000	857,600	8,224.8	4,768.5	4,768.5	3,814.8
18.625	117.5	J-55	BTC	1,849,000	1,795,000	1,795,000	1,436,000	8,224.8	7,984.6	7,984.6	6,387.6
18.625	117.5	K-55	STC	1,849,000	1,129,000	1,129,000	903,200	8,224.8	5,022	5,022	4,017.6
18.625	117.5	K-55	BTC	1,849,000	1,929,000	1,849,000	1,479,200	8,224.8	8,580.6	8,224.8	6,579.8
18.625	117.5	N-80	STC	2,689,000	1,534,000	1,534,000	1,227,200	11,961.3	6,823.6	6,823.6	5,458.9
18.625	117.5	N-80	BTC	2,689,000	2,551,000	2,551,000	2,040,800	11,961.3	11,347.4	11,347.4	9,077.9
20	94	H-40	STC	1,077,000	581,000	581,000	464,800	4,790.7	2,584.4	2,584.4	2,067.5
20	94	H-40	BTC	1,077,000	1,041,000	1,041,000	832,800	4,790.7	4,630.6	4,630.6	3,704.5
20	94	J-55	STC	1,480,000	783,000	783,000	626,400	6,583.4	3,483	3,483	2,786.4
20	94	J-55	LTC	1,480,000	907,000	907,000	725,600	6,583.4	4,034.5	4,034.5	3,227.6

Check every figure against your own pipe records before you pull.

Casingjacks

Casingjacks LLC | sales@casingjack.com

Max pull tables

Data version 1.326cfcf0 | Build date 2026-11-17

Max pull

OD in	Weight lb/ft	Grade	Connection	Body lb	Joint lb	Lesser lb	P_allow lb	Body kN	Joint kN	Lesser kN	P_allow kN
20	94	J-55	BTC	1,480,000	1,402,000	1,402,000	1,121,600	6,583.4	6,236.4	6,236.4	4,989.1
20	94	K-55	STC	1,480,000	824,000	824,000	659,200	6,583.4	3,665.3	3,665.3	2,932.3
20	94	K-55	LTC	1,480,000	955,000	955,000	764,000	6,583.4	4,248.1	4,248.1	3,398.4
20	94	K-55	BTC	1,480,000	1,479,000	1,479,000	1,183,200	6,583.4	6,578.9	6,578.9	5,263.1
20	106.5	J-55	STC	1,685,000	913,000	913,000	730,400	7,495.3	4,061.2	4,061.2	3,249
20	106.5	J-55	LTC	1,685,000	1,056,000	1,056,000	844,800	7,495.3	4,697.3	4,697.3	3,757.9
20	106.5	J-55	BTC	1,685,000	1,595,000	1,595,000	1,276,000	7,495.3	7,094.9	7,094.9	5,675.9
20	106.5	K-55	STC	1,685,000	960,000	960,000	768,000	7,495.3	4,270.3	4,270.3	3,416.2
20	106.5	K-55	LTC	1,685,000	1,113,000	1,113,000	890,400	7,495.3	4,950.9	4,950.9	3,960.7
20	106.5	K-55	BTC	1,685,000	1,683,000	1,683,000	1,346,400	7,495.3	7,486.4	7,486.4	5,989.1
20	106.5	N-80	STC	2,450,000	1,307,000	1,307,000	1,045,600	10,898.1	5,813.8	5,813.8	4,651.1
20	106.5	N-80	LTC	2,450,000	1,514,000	1,514,000	1,211,200	10,898.1	6,734.6	6,734.6	5,387.7
20	106.5	N-80	BTC	2,450,000	2,281,000	2,281,000	1,824,800	10,898.1	10,146.4	10,146.4	8,117.1
20	133	K-55	STC	2,125,000	1,253,000	1,253,000	1,002,400	9,452.5	5,573.6	5,573.6	4,458.9
20	133	K-55	LTC	2,125,000	1,453,000	1,453,000	1,162,400	9,452.5	6,463.3	6,463.3	5,170.6
20	133	K-55	BTC	2,125,000	2,123,000	2,123,000	1,698,400	9,452.5	9,443.6	9,443.6	7,554.9
20	133	L-80	STC	3,091,000	1,692,000	1,692,000	1,353,600	13,749.5	7,526.4	7,526.4	6,021.1
20	133	L-80	LTC	3,091,000	1,958,000	1,958,000	1,566,400	13,749.5	8,709.6	8,709.6	6,967.7
20	133	L-80	BTC	3,091,000	2,849,000	2,849,000	2,279,200	13,749.5	12,673	12,673	10,138.4
20	133	N-80	STC	3,091,000	1,707,000	1,707,000	1,365,600	13,749.5	7,593.1	7,593.1	6,074.5
20	133	N-80	LTC	3,091,000	1,976,000	1,976,000	1,580,800	13,749.5	8,789.7	8,789.7	7,031.7
20	133	N-80	BTC	3,091,000	2,877,000	2,877,000	2,301,600	13,749.5	12,797.5	12,797.5	10,238
20	169	K-55	STC	2,692,000	1,402,000	1,402,000	1,121,600	11,974.6	6,236.4	6,236.4	4,989.1
20	169	K-55	LTC	2,692,000	1,732,000	1,732,000	1,385,600	11,974.6	7,704.3	7,704.3	6,163.5
20	169	K-55	BTC	2,692,000	2,689,000	2,689,000	2,151,200	11,974.6	11,961.3	11,961.3	9,569

Check every figure against your own pipe records before you pull.

Casingjacks

Casingjacks LLC | sales@casingjack.com

Max pull tables

Data version 1.326cfcf0 | Build date 2026-11-17

Max pull

OD in	Weight lb/ft	Grade	Connection	Body lb	Joint lb	Lesser lb	P_allow lb	Body kN	Joint kN	Lesser kN	P_allow kN
20	169	L-80	STC	3,916,000	2,202,000	2,202,000	1,761,600	17,419.2	9,795	9,795	7,836
20	169	L-80	LTC	3,916,000	2,549,000	2,549,000	2,039,200	17,419.2	11,338.5	11,338.5	9,070.8
20	169	L-80	BTC	3,916,000	3,610,000	3,610,000	2,888,000	17,419.2	16,058.1	16,058.1	12,846.5
20	169	N-80	STC	3,916,000	2,221,000	2,221,000	1,776,800	17,419.2	9,879.5	9,879.5	7,903.6
20	169	N-80	LTC	3,916,000	2,573,000	2,573,000	2,058,400	17,419.2	11,445.3	11,445.3	9,156.2
20	169	N-80	BTC	3,916,000	3,645,000	3,645,000	2,916,000	17,419.2	16,213.8	16,213.8	12,971

F9 Max pull on the string. Max safe pull = lesser of pipe-body yield (the row's sheet value, F3) and the joint strength of the chosen connection, divided by the design factor: P_allow = min(P_y, P_joint) / DF (default DF 1.25 = 80%). If the connection is "not sure", use the lowest joint strength the row lists.

• 9-5/8" 40# N-80, LTC: min(916,000, 737,000) / 1.25 = 589,600 lb. BTC: min(916,000, 979,000) / 1.25 = 732,800 lb.

• 5-1/2" 17# N-80, LTC: min(397,000, 348,000) / 1.25 = 278,400 lb.

P_allow is the lesser of pipe body yield and joint strength divided by the design factor; 1.25 here. Pick your own factor in the max pull calculator.

No joint strength is listed, so this limit uses pipe body yield only. Your connection may be weaker.

Slips can crush pipe before it reaches its rated pull. Slip-crush capacity for your pipe is set when the jack is engineered for your order; the relief is set to the lower limit.